

Switch TELTONIKA 4xRJ-45 ports RJ-45 Ports Type Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Yes TSW304

Model: TSW304

Manufacturer: TELTONIKA

EAN: 4779051840144

Product Code: 772148

R2,181

DIN RAIL SWITCH

TSW304 is the tiniest switch in the Teltonika Networks portfolio, made with the industrial application scenarios in mind. This ultra-small device comes with an integrated DIN rail mounting option and will easily find its place in any server cabinet. Durable design and shock-resistant casing make it perfect for even the most challenging industrial environments.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

MOUNTING

Integrated DIN rail bracket and surface mounting options

COMPACT

102 x 25 x 81.5 mm

GIGABIT ETHERNET

4 x Gigabit Ethernet with speeds of up to 1000 Mbps

7-57 V

Wide range of supported power supply voltages

Summary: Teltonika TSW304. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 4. MAC address table: 2000 entries, Switching capacity: 8 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3az, IEEE 802.3u. DC input voltage: 7 - 57 V. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: https://teltonika-networks.com/products/switches/tsw304 | Basic switching RJ-45 Ethernet ports quantity: 4 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3/IEEE 802.3az/IEEE 802.3u | 10G support: No | Auto MDI/MDI-X: Yes | Ethernet LAN data rates: 10,100,1000 | Switching capacity: 8 | MAC address table: 2000 | Jumbo frames support: Yes | Jumbo frames: 9216 | Packet buffer memory: 0.128 | Product colour: Black | Housing material: Aluminium | LED indicators: Power/Status | DIN rail mounting: Yes | International Protection (IP) code: IP30 | Wall mountable: Yes | Power source: AC/DC | DC input voltage: 7 - 57 | Input voltage: 9 - 40 | Power consumption (typical): 0.26 | Power consumption (max): 1.44 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Operating temperature (T-T): -40 - 75 | Operating relative humidity (H-H): 10 - 90 | Width: 102 | Depth: 81.5 | Height: 25 | Weight: 210 | Certification: CE, REACH, RoHS, WEEE, UKCA, FCC, IC, CB, RCM | Unit Calculated Weight: 0.23 | Product Net Weight: 0.21 | Unit Calculated Volume: 0.00033 | Units per Shipping Box: 1 | Unit Width: 11 | Units per Pallet: 0 | Shipping Box Height: 3 | Unit Depth: 10 | Unit Height: 3 | Name: NET SWITCH 4PORT 10/100/1000/TSW304 TELTONIKA | Model: TSW304 | Model name: TSW304

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950