



Access Point MIKROTIK IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac RBCAPGI- 5ACD2ND

Model: RBCAPGI-5ACD2ND

Manufacturer: MIKROTIK

EAN: 4752224003416

Product Code: 772168

R2,203

The cAP ac is a very capable and powerful wireless access point that looks beautiful on both walls and ceilings. The concurrent dual band wireless radio supports dual chain 2 GHz 802.11b/g/n and 5 GHz in a/n/ac standards, and will provide coverage in 360 degrees around it.

Even though the radio supports repeater mode, the two Ethernet ports give you the ability to extend your network with cables, even if PoE power is required, since the cAP ac supports 802.3af/at PoE input on the first port, and passive PoE output on the second port. Device supports IPsec hardware

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

acceleration too.

The cAP ac is a feature packed device with a sleek enclosure, that can become inconspicuous with the push of a button - the customizable mode button in the device center will turn off all lights and sounds at it's default configuration, but can be reconfigured to launch any RouterOS script.

Summary: Mikrotik cAP ac. 2.4 GHz, 5 GHz, Maximum data transfer rate: 867 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 13 W | Vendor Homepage: https://mikrotik.com/product/cap_ac#fndtn-specifications | 2,4 GHz: Taip | 5 GHz: Taip | Didžiausias duomenų perdavimo greitis: 867 | Maksimalus duomenų perdavimo greitis (2,4 GHz): 300 | Maksimalus duomenų perdavimo greitis (5 GHz): 867 | Eterneto LAN duomenų perdavimo norma: 10/100/1000 | Dažnių juosta: 2.412 - 2.484, 5.15 - 5.875 | Tinklo standartai: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.3af/IEEE 802.3at | Imtuvo jautrumas: 2.4GHz: 1MBit/s: -100 @ 26dBm Tx 11MBit/s: -94 @ 26dBm Tx 6MBit/s: -96 @ 26dBm Tx 54MBit/s: -78 @ 23dBm Tx MCS0: -96 @ 26dBm Tx MCS7: -73 @ 22dBm Tx 5GHz: 6MBit/s: -96 @ 26dBm Tx 54MBit/s: -80 @ 21dBm Tx MCS0: -96 @ 26dBm Tx MCS7: -75 @ 20dBm Tx MCS9: -7 | Ethernet LAN (RJ-45) portų kiekis: 2 | Maitinimas per Eternetą (PoE): Taip | Palaikomas maitinimo per eternetą (en. PoE) tipas: Active PoE/Passive PoE | DC įtampos stiprumo intervalas: 17 - 57 | Išėjimo įtampa: 57 | Galios suvartojimas (maks.): 13 | Talpinimo: Ceiling,Wall | Produkto spalva: Balta | LED indikatoriai: Taip | Vidinis: Ne | Antenos tipas: Vidinis | Antenos ypatybės: Integruota antena | Antenų kiekis: 4 | Antenos stiprinimo lygis (max): 2.5 | Integruotas procesorius: Taip | Procesoriaus modelis: IPQ4018 | Procesoriaus dažnis: 716 | Flash atmintis: 16 | Vidinė atmintis: 128 | Numatyta operacinė sistema: RouterOS | Sertifikavimas: CE, FCC, IC, EAC, ROHS | Plotis: 136 | Ilgis: 30 | Aukštis: 136 | Kintamosios srovės adapteris: Taip | Pridėtas PoE adapteris: Taip | Montavimo rinkinys: Taip | Darbo temperatūros diapazonas (TT): -40 - 50 | Darniosios sistemos (DS) kodas: 85176990 | Bruto svoris: 0.718 | Neto svoris: 0.2 | Vienetų skaičius vienoje siuntimo dėžėje: 20 | Vieneto plotis: 18 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 30 | Vieneto gylis: 6 | Vieneto aukštis: 26.5 | Name: WRL ACCESS POINT 5GHZ/RBCAPGI-5ACD2ND MIKROTIK | Model name: cAP ac // RBcAPGi-5acD2nD

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](mailto:sales@cssi.co.za) | sales@cssi.co.za | +27 (11)541-9950