

WRL ACCESS POINT/DAP140 TELTONIKA



Model: DAP140

Manufacturer: TELTONIKA

EAN: 4779051843251

Product Code: 772269

R1,955

The DAP140 is a Teltonika industrial wireless access point with passive PoE-in, designed to enhance Wi-Fi coverage and performance in industrial environments. Featuring Wi-Fi 4 with Wi-Fi mesh and Fast Roaming, as well as dual RJ45 ports and support of up to 50 simultaneous connections, this wireless access point is integral in maintaining reliable connectivity. An integrated DIN rail bracket, 3-pin power connector, and industrial-grade aluminium housing make the DAP140 the ideal access point for industrial applications.

- Seamless Wi-Fi 4 with Wi-Fi mesh & Fast Roaming
- 2 x 10/100 RJ45
- 1 x 3-pin power connector tailored for industrial use
- Easy mounting for plug-and-play deployment

Summary: Teltonika DAP140. 2.4 GHz, Maximum data transfer rate: 300 Mbit/s. Security algorithms: OWE, WPA-EAP, WPA-PSK, WPA2-EAP, WPA2-PSK, WPA3-EAP, WPA3-SAE. Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: Black | Vendor Homepage:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

<https://teltonika-networks.com/products/access-points/DAP140/> | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No | Cabling technology: 10/100Base-T(X) | Ethernet LAN data rates: 10/100/1000 | Fast roaming: Yes | Maximum data transfer rate: 300 | Maximum data transfer rate (2.4 GHz): 300 | Networking standards: IEEE 802.11b/IEEE 802.11e/IEEE 802.11g/IEEE 802.11k/IEEE 802.11n/IEEE 802.11r/IEEE 802.11s/IEEE 802.11v/IEEE 802.3/IEEE 802.3az/IEEE 802.3u | Wireless meshing: Yes | MAC address filtering: Yes | Security algorithms: OWE/WPA2-EAP/WPA2-PSK/WPA3-EAP/WPA3-SAE/WPA-EAP/WPA-PSK | VPN support: OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard, Tinc, Tailscale | DHCP client: Yes | DHCP server: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Supported network protocols: TCP, UDP, IPv4, IPv6, NTP, DNS, HTTP, HTTPS, FTP, SMTP, SSL/TLS, ARP, VRRP, PPP, PPPoE, UPNP, SSH, DHCP, Telnet, SNMP, MQTT, Wake On Lan (WOL) | Universal Plug and Play (UPnP): Yes | Command-line interface (CLI): Yes | Web-based management: Yes | Ethernet LAN (RJ-45) ports: 2 | RS-232 interface: No | WAN connection: Ethernet (RJ-45) | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Housing material: Aluminium | International Protection (IP) code: IP30 | LED indicators: Power | Placement: Shelf,Wall | Product colour: Black | Reset button: Yes | Antenna connector type: RP-SMA | Antenna type: External | Built-in processor: Yes | Flash memory: 128 | Internal memory: 16 | Operating system installed: RutOS | Processor frequency: 580 | Depth: 68.6 | Height: 25 | Weight: 150 | Width: 113.1 | Quantity per pack: 1 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Storage relative humidity (H-H): -50 - 75 | Storage temperature (T-T): 10 - 90 | Product Net Weight: 0.1423 | Shipping Box Height: 17 | Unit Calculated Volume: 0.0011794 | Unit Calculated Weight: 0.259 | Units per Shipping Box: 20 | Model name: DAP140000000

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950