



Access Point MIKROTIK IEEE 802.11b IEEE 802.11g IEEE 802.11n 1xUSB 2.0 5x10/100M RB951UI-2HND

Model: RB951UI-2HND

Manufacturer: MIKROTIK

EAN: 4752224001146

Product Code: 772407

R1,713

The RB951Ui-2HnD is a wireless SOHO AP with a new generation Atheros CPU and more processing power. It has five Ethernet ports, one USB 2.0 port and a high power 2.4GHz 1000mW 802.11b/g/n wireless AP with antennas built in.

It has a 600MHz CPU, 128MB of RAM and PoE output function for port #5 - it can power other PoE capable devices with the same voltage as applied to the unit. Maximum load on the port is 500mA.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Package contains RouterBOARD 951Ui-2HnD in a plastic case and power adapter.

Summary: Mikrotik RB951Ui-2HnD. 2.4 GHz, Ethernet LAN data rates: 10,100 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 7 W | Vendor Homepage: <https://routerboard.com/RB951Ui-2HnD> | 2,4 GHz: Taip | Ethernet LAN duomenų perdavimo norma: 10/100 | Dažnių juosta: 2.4 | Tinklo standartai: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.3/IEEE 802.3u | Moduliacija: 16-QAM/64-QAM/BPSK/CCK/DBPSK/DQPSK/DSSS/OFDM/QPSK | Imtuvo jautrumas: 802.11g: -96dBm @ 6Mbit/s to -80dBm @ 54Mbit/s 802.11n: -96dBm @ MCS0 to -78dBm @ MCS7 | Ethernet LAN (RJ-45) portų kiekis: 5 | USB 2.0 portų kiekis: 1 | USB jungtis: USB A tipo | Maitinimas per Ethernetą (PoE): Taip | AC įėjimo įtampa: 7 - 31 | Galios suvartojimas (maks.): 7 | Produkto spalva: Balta | Korpuso medžiaga: Plastikis | LED indikatoriai: Taip | Vidinis: Ne | Antenos tipas: Vidinis | Antenos stiprinimo lygis (max): 2.5 | Integruotas procesorius: Taip | Procesoriaus modelis: Qualcomm Atheros AR9344-DC3A | Procesoriaus dažnis: 600 | Vidinė atmintis: 128 | Vidinės atminties tipas: DDR2 | Plotis: 138 | Ilgis: 113 | Aukštis: 29 | Siejama programinė įranga: MikroTik RouterOS | Darbo temperatūros diapazonas (TT): -20 - 50 | Darniosios sistemos (DS) kodas: 85176990 | Bruto svoris: 0.43 | Neto svoris: 0.232 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 6 | Shipping Box Height: 14.5 | Vieneto gylis: 20 | Vieneto aukštis: 14.5 | Name: WRL ACCESS POINT 2.4GHZ/RB951UI-2HND MIKROTIK | Model name: RB951Ui-2HnD // RB951Ui-2HnD

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950