



Access Point TP-LINK 1200 Mbps IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac 1x10/100/1000M TL-WA1201



Model: TL-WA1201

Manufacturer: TP-LINK

EAN: 6935364084035

Product Code: 772479

R1,691

- AC1200 Dual-Band Wi-Fi – Fast Wi-Fi 5 speed in both 5 GHz and 2.4 GHz
- Flexible Deployment – Supports Passive PoE to carry electrical power and data simultaneously
- Multiple Modes – Supports Access Point, Range Extender, Multi-SSID, and Client modes to meet any network needs

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- MU-MIMO Technology – Simultaneously transfers data to multiple devices for 2× faster performance
- Boosted Coverage – Four fixed antennas equipped with Beamforming technology extend and concentrate the Wi-Fi signals
- Captive Portal – Offers a designed portal page for heightened security and marketing

Summary: TP-Link TL-WA1201. 2.4 GHz, 5 GHz, Maximum data transfer rate: 867 Mbit/s. Security algorithms: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White | Vendor Homepage: <https://www.tp-link.com/uk/home-networking/access-point/tl-wa1201/#overview> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Ethernet LAN data rates: 10/100/1000 | Maximum data transfer rate: 867 | Maximum data transfer rate (2.4 GHz): 300 | Maximum data transfer rate (5 GHz): 867 | MIMO: Yes | MIMO type: Multi User MIMO | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11b/IEEE 802.11g/IEEE 802.11n | Quality of Service (QoS) support: Yes | Transmitting power (CE): 20 - 23 | Transmitting power (FCC): 30 | Virtual LAN features: Multicast VLAN | VLAN support: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Access Control List (ACL): Yes | Auto Wireless Distribution System (WDS): Yes | Security algorithms: 128-bit WEP/64-bit WEP/WPA/WPA2/WPA2-PSK/WPA-PSK | Service Set Identifier (SSID) features: Multiple SSIDs | DHCP client: Yes | DHCP server: Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Universal Plug and Play (UPnP): Yes | Ethernet LAN (RJ-45) ports: 1 | Output current: 1.5 | Output voltage: 12 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Active PoE | On/off switch: Yes | Placement: Table | Product colour: White | Reset button: Yes | WPS push button: Yes | Antenna type: External | Antennas quantity: 4 | Compatible operating systems: Microsoft Windows 98SE, NT, 2000, XP, Vista or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Depth: 145.5 | Height: 37 | Width: 225 | Package depth: 255 | Package height: 69 | Package weight: 860 | Package width: 400 | AC adapter included: Yes | Cables included: LAN (RJ-45) | PoE adapter included: Yes | Quantity per pack: 1 | Quick start guide: Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 10 - 90 | Storage temperature (T-T): -40 - 70 | Sustainability compliance: Yes | Product Net Weight: 0.76 | Shipping Box Height: 25.6 | Unit Calculated Volume: 0.007494 | Unit Calculated Weight: 0.912 | Units per Shipping Box: 1 | Model name: TL-WA1201

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950