

Dahua Technology S3016-16GT network switch Unmanaged L2 Gigabit Ethernet (10/100/1000) Desktop/Wall- Mounting Black



Model: S3016-16GT

Manufacturer: DAHUA

EAN: 6939554932632

Product Code: 772492

R1,589

- > 16 × RJ-45 10/100/1000 ports.
- > The all-gigabit ports transmit data without lag.
- > Features aggregation mode which aggregates uplink ports.
- > Features isolation mode which isolates all the ports from each other.
- > With its solid full metal design, the device has great heat dissipation and no fan.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- > Supports rack mount, wall mount and desktop mount.

Summary: Dahua Technology S3016-16GT. Switch type: Unmanaged, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. MAC address table: 16000 entries, Switching capacity: 32 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Rack mounting, Form factor: Desktop/Wall-Mounting | Vendor Homepage: <https://transmission.dahuasecurity.com/fr/product-list/Business/Switches/AccessSwitch/S3016-16GT> | Switch layer: L2 | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | 10G support: No | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3u | Forwarding rate: 23.8 | Jumbo frames: 12000 | Jumbo frames support: Yes | MAC address table: 16000 | Packet buffer memory: 8.4 | Switching capacity: 32 | Form factor: Desktop/Wall-Mounting | Housing material: Metal | LED indicators: Yes | Product colour: Black | Rack mounting: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Input current: 0.4 | Power consumption (typical): 7.8 | Power source: DC | Power supply included: Yes | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Depth: 119 | Height: 44 | Weight: 740 | Width: 294 | Package depth: 215 | Package height: 75 | Package weight: 1297 | Package width: 353 | Product Net Weight: 0.74 | Shipping Box Height: 7.5 | Unit Calculated Volume: 0.005724 | Unit Calculated Weight: 1.4 | Units per Shipping Box: 1 | Model name: S3016-16GT

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950