

**Switch DAHUA
DH-CS4010-
8ET2GT-60
Switch layer L2
8xRJ-45 ports RJ-
45 Ports Type
Fast Ethernet
(10/100)
2xGigabit
Ethernet
(copper) ports
quantity
8xPower over
Ethernet (PoE)
ports quantity
Total Power
over Ethernet
(PoE) budget 60
W CS4010-
8ET2GT-60**



Model: CS4010-8ET2GT-60

Manufacturer: DAHUA

EAN: 6937552421417

Product Code: 772508

R1,557

- 8 × RJ-45 10/100 Mbps PoE ports, 2 × RJ-45 Gigabit ports
- 60 W total PoE budget, 802.3af/at on all PoE ports, additional Hi-PoE on orange port
- DIP switch to fast turn on/off working mode of Cloud-Managed, PoE Watchdog, Long Distance PoE
- Wide operating temperature ranging from -10 °C to 55 °C
- Supports VLAN and loop protection
- WEB-managed and centralized cloud management through the DoLink App and performs real-time monitoring of the network
- Easy config to auto detect and set up network and security systems

Summary: Dahua Technology CS4010-8ET2GT-60. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 8000 entries, Switching capacity: 5.6 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3az, IEEE.... DC input voltage: 53 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://transmission.dahuasecurity.com/en/product-list/business/cloudmanagementsolution/networkswitch/cs4010-8et2gt-60> | Cloud-managed: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Fast Ethernet (copper) ports quantity: 8 | Gigabit Ethernet (copper) ports quantity: 2 | Power connector: DC-in jack | 10G support: No | Broadcast storm control: Yes | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Networking standards: IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3u/IEEE 802.3x | Number of VLANs: 32 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Port mirroring: Yes | VLAN support: Yes | Forwarding rate: 4.17 | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 4 | Switching capacity: 5.6 | DHCP features: DHCP client | IP-MAC-Port binding: Yes | Loop protection: Yes | Multicast support: Yes | Housing material: Metal | LED indicators: Yes | Product colour: Blue | Rack mounting: No | Reset button: Yes | Wall mountable: Yes | Mean time between failures (MTBF): 2837361 | DC input voltage: 53 | Input current: 1.22 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Total Power over Ethernet (PoE) budget: 60 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 184.6 | Height: 27 | Weight: 360 | Width: 103.3 | Cables included: AC | Manual: Yes | Package depth: 252 | Package height: 113 | Package weight: 920 | Package width: 137 | Compliance certificates: CE | Product Net Weight: 0.36 | Shipping Box Height: 25 | Unit Calculated Volume: 0.004615 | Unit Calculated Weight: 1 | Units per Pallet: 0 | Units per Shipping Box: 20 | Model name: CS4010-8ET2GT-60

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950