



Access Point TP-LINK 300 Mbit/s 1xLAN ports 2xAntennas quantity EAP110-OUTDOOR

Model: EAP110-OUTDOOR

Manufacturer: TP-LINK

EAN: 6935364097752

Product Code: 772521

R1,531

Enjoy Wi-Fi Outside, Finally

Omada EAP110-Outdoor

Excellent Hardware Designs

With special design of its antenna, appearance, power options and installation methods, EAP110-Outdoor can perfectly fit for different scenarios both indoors and outdoors.

Detachable Antennas

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

EAP110-Outdoor is designed with 2 Omni-directional detachable antennas, which means other antennas can also be attached for your specific demands.

Delicate Appearance Even Better for Indoor Applications

EAP110-Outdoor is just similar to a cellphone, with dimension: 8.5 × 1.8 × 1.1in. (215 × 46 × 27mm)

Supports Passive PoE for Easy Outdoor Set up

Do away with DC power adapters and power cords with passive Power over Ethernet (PoE), making outdoor deployment simple and fast.

Flexible Deployment

EAP110-Outdoor can be easily installed to a pole or on a wall with the mounting kits provided.

Wi-Fi That Goes the Distance

With high transmission power and two high-gain omnidirectional antennas, EAP110-Outdoor provides stable wireless coverage at a range of up to 200 meters* in outdoor settings.

Specially Designed Weatherproof Enclosure for Outdoor Environment

Rated as IP65 during Ingress Protection testing, a resilient weatherproof enclosure protects the access points against harsh outdoor condition.

Cloud Centralized Management

- Anytime, Anywhere

Omada Hardware Controller OC200 and Omada Software Controller make it easy to manage and monitor the whole Omada network in real-time, while cloud service enables remote and secure access no matter where you find yourself.

Easy Management with the Omada App

Follow configuration instructions on the free Omada app to get set up in minutes. Omada lets you configure settings, monitor the network status and manage clients, all from the convenience of a smart phone or tablet.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Built for outdoor Wi-Fi applications
- Up to 300Mbps Wi-Fi with 2x2 MIMO technology
- High transmission power and high gain antennas provide a long-range coverage area
- Durable, weatherproof enclosure to withstand fair and foul weather
- Passive PoE(Power over Ethernet) support and simple mounting design allow for flexible deployment and convenient installation
- Cloud centralized management and Omada app for ultra convenience and easy management
- Secure guest network along with multiple authentication options (SMS/Facebook Wi-Fi/Voucher, etc.) and abundant wireless security technologies
- Supports management vlan for an enhanced network management

Summary: TP-Link Omada 300Mbps Wireless N Outdoor Access Point. 2.4 GHz, Maximum data transfer rate: 300 Mbit/s. Security algorithms: WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK. Ethernet LAN data rates: 10,100 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 3.12 W | Vendor Homepage: <https://www.tp-link.com/uk/business-networking/outdoor-ap/eap110-outdoor/> | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No | Maximum data transfer rate: 300 | Maximum data transfer rate (2.4 GHz): 300 | Ethernet LAN data rates: 10/100 | Frequency band: 2.4 | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n | Automatic channel selection: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | VLAN support: Yes | Virtual LAN features: Tagged VLAN/VLAN mapping | Rate limiting: Yes | Wireless isolation: Yes | Quality of Service (QoS) support: Yes | Transmitting power (CE): 20 | Transmitting power (FCC): 22 | Security algorithms: WPA2-Enterprise/WPA2-PSK/WPA-Enterprise/WPA-PSK | MAC address filtering: Yes | Service Set Identifier (SSID) features: Multiple SSIDs | Number of SSID supported: 8 | Remote Authentication Dial-In User Service (RADIUS): Yes | Access Control List (ACL): Yes | Management protocols: HTTP/HTTPS, SNMP, Telnet | Web-based management: Yes | Syslog: Yes | Ethernet LAN (RJ-45) ports: 1 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Output voltage: 24 | Output current: 0.6 | Power consumption (max): 3.12 | Placement: Pole,Wall | Product colour: White | International Protection (IP) code: IP65 | Reset button: Yes | LED indicators: Power | Antenna type: External | Antenna direction type: Omni-directional | Antenna features: Detachable antenna | Antennas quantity: 2 | Antenna gain level (max): 3 | Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10 | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Certification: CE, FCC, RoHS | Width: 216 | Depth: 46 | Height: 27 | Package width: 140 | Package depth: 270 | Package height: 100 | Package weight: 620 | Package type: Box | Quantity per pack: 1 | PoE adapter included: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](mailto:sales@cssi.co.za) | sales@cssi.co.za | +27 (11)541-9950

Cables included: AC | Mounting kit: Yes | Antenna included: Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -30 - 65 | Storage temperature (T-T): -40 - 70 | Storage relative humidity (H-H): 5 - 90 | Sustainability compliance: Yes | Unit Calculated Weight: 0.665 | Product Net Weight: 0.358 | Unit Calculated Volume: 0.004448 | Units per Shipping Box: 20 | Unit Width: 14 | Units per Pallet: 0 | Shipping Box Height: 30.2000007629395 | Unit Depth: 27 | Unit Height: 10 | Name: WRL ACCESS POINT 300MBPS/OMADA EAP110-OUTDOOR TP-LINK | Model name: 300Mbps Wireless N Outdoor Access Point

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950