



Access Point MIKROTIK IEEE 802.11b IEEE 802.11g IEEE 802.11n 1xRJ45 RBCAP2ND

Model: RBCAP2ND

Manufacturer: MIKROTIK

EAN: 4752224001191

Product Code: 772528

R1,532

RouterBOARD cAP-2nD (ceiling Access Point) is our first 2.4GHz Dual-Chain ceiling AP.

Inconspicuously designed, it blends into the environment, perfect for hospitality business like hotels, airports, shopping malls etc.

cAP-2nD supports 802.11b/g/n and can be powered by PoE. It's a perfect companion for the MikroTik CAPsMAN (controlled AP system manager), allowing you to control all your AP devices from one central location.

Unlike traditional controller software, which requires a separate PC/Mac to run, our CAPsMAN runs on any existing RouterBOARD device in your network. No need for a separate controller machine.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Everything is included to get you started, wall/ceiling mount, PoE injector, power adapter and even the screws and screw anchors.

Summary: Mikrotik cAP-2nD. 2.4 GHz, Ethernet LAN data rates: 10,100 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 4 W | Vendor Homepage:

<https://mikrotik.com/product/RBcAP2nD> | 2.4 GHz: Yes | 5 GHz: No | Auto MDI/MDI-X: Yes | Ethernet LAN data rates: 10/100 | Frequency band: 2.4 | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.3af/IEEE 802.3at | Receiver sensitivity: 1MBit/s: -96 @ 22dBm Tx 11MBit/s: -89 @ 22dBm Tx 6MBit/s: -93 @ 20dBm Tx 54MBit/s: -74 @ 18dBm Tx MCS0: -93 @ 20dBm Tx MCS7: -71 @ 26dBm Tx | Transmitting power: 22 | Wi-Fi data rate (max): 54 | Ethernet LAN (RJ-45) ports: 1 | AC input voltage: 11 - 57 | Power consumption (max): 4 | Power over Ethernet (PoE): Yes | Internal: No | LED indicators: Yes | Placement: Ceiling | Product colour: White | Antenna gain level (max): 2 | Built-in processor: Yes | Flash memory: 16 | Internal memory: 64 | Operating system installed: RouterOS | Depth: 138 | Height: 31 | Width: 138 | AC adapter included: Yes | Mounting kit: Yes | PoE adapter included: Yes | Operating temperature (T-T): -40 - 70 | Product Net Weight: 0.25 | Shipping Box Height: 38 | Unit Calculated Volume: 0.001757 | Unit Calculated Weight: 0.505 | Units per Pallet: 590 | Units per Shipping Box: 20 | Model name: cAP // RBcAP2nD

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950