

Dahua Technology PFS3008-8GT-96 network switch Unmanaged L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Model: CS4006-4ET2GT-36

Manufacturer: DAHUA

EAN: 6939554912986

Product Code: 772667

R1,312

- 4 × RJ45 10/100 Mbps PoE ports, 2 × RJ45 Gigabit ports
- 36 W total PoE budget, 802.3af/at on all PoE ports

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- DIP switch to fast turn on/off working mode of Cloud-Managed, PoE Watchdog, Long Distance PoE
- Wide operating temperature ranging from -10 °C to 55 °C
- Supports VLAN and loop protection
- WEB-managed and centralized cloud management through the DoLink App and performs real-time monitoring of the network
- Easy config to auto detect and set up network and systems

Summary: Dahua Technology PoE CS4006-4ET2GT-36. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 6. MAC address table: 2000 entries, Switching capacity: 4.8 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3, IEEE 802.3x, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3az, IEEE.... DC input voltage: 53 V. Power connector: DC-in jack. Power over Ethernet (PoE).

Form factor: Desktop/Wall-Mounting | Vendor Homepage:

<https://transmission.dahuasecurity.com/en/product->

[list/Business/CloudManagementSolution/NetworkSwitch/CS4006-4ET2GT-36](https://transmission.dahuasecurity.com/en/product-list/Business/CloudManagementSolution/NetworkSwitch/CS4006-4ET2GT-36) | Cloud-managed: Yes | Switch layer: L2 | Switch type: Managed | System event log: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 6 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Fast Ethernet (copper) ports quantity: 4 | Gigabit Ethernet (copper) ports quantity: 2 | Power connector: DC-in jack | 10G support: No | Broadcast storm control: Yes | Flow control support: Yes | Networking standards: IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3u/IEEE 802.3x | Number of VLANs: 32 | Port mirroring: Yes | VLAN support: Yes | Forwarding rate: 3.57 | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 2000 | Packet buffer memory: 4 | Switching capacity: 4.8 | DHCP features: DHCP client | Form factor: Desktop/Wall-Mounting | Housing material: Metal | LED indicators: Yes | Product colour: Blue | Rack mounting: No | Reset button: Yes | Mean time between failures (MTBF): 2039146.92 | DC input voltage: 53 | Input current: 0.8 | Power consumption (max): 42.4 | Power source: DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 4 | Total Power over Ethernet (PoE) budget: 36 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 115 | Height: 27 | Weight: 200 | Width: 84 | Cables included: AC | Package depth: 195 | Package height: 83 | Package weight: 720 | Package width: 114 | Compliance certificates: CE | Product Net Weight: 0.2 | Shipping Box Height: 29.5 | Unit Calculated Volume: 0.002621 | Unit Calculated Weight: 0.746 | Units per Pallet: 0 | Units per Shipping Box: 12 | Model

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

name: CS4006-4ET2GT-36

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950