



Access Point TP-LINK Omada 300 Mbps IEEE 802.11b IEEE 802.11g IEEE 802.11n 1xRJ45 Number of antennas 2 EAP110

Model: EAP110

Manufacturer: TP-LINK

EAN: 6935364091620

Product Code: 772696

R1,271

Flexible Placement

Easy mounting design & PoE

The EAP's elegant appearance and easy mounting design with chassis make it easy to be integrated seamlessly into any wall or ceiling surface to blend in with most interior decorations. EAP110 supports Passive PoE to make deployment effortless and flexible.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Cloud Centralized Management - Anytime, Anywhere

Omada Cloud Controller OC200 and Omada Software Controller make it easy to manage and monitor the whole Omada network in real-time, while cloud service enables remote and secure access no matter where you find yourself.

Captive Portal

Guest Network with Facebook and SMS Support

The captive portal helps maintain only authorized guests to use the network, presenting devices with a convenient, user-friendly authentication method to grant Wi-Fi access. The addition of SMS and Facebook authentication simplifies the captive portal even further to simplify connectivity and boost your business.

Easy Management with the Omada App

Follow configuration instructions on the free Omada app to get set up in minutes. Omada lets you configure settings, monitor the network status and manage clients, all from the convenience of a smartphone or tablet.

- Cloud centralized management and Omada app for ultra convenience and easy management
- Supports passive PoE for convenient installation up to 100meters
- Ceiling mounting design with chassis make it easy to deploy on a wall or ceiling
- Secure guest network along with multiple authentication options (SMS/Facebook Wi-Fi/Voucher, etc.) and abundant wireless security technologies
- Multi-SSID divides multiple wireless networks for different users
- Enterprise class Wi-Fi security help to decrease network security threats
- Supports management vlan for an enhanced network management

Summary: TP-Link Omada 300Mbps Wireless N Ceiling Mount Access Point. 2.4 GHz, Maximum data transfer rate: 300 Mbit/s. Security algorithms: 64-bit WEP, 128-bit WEP, 152-bit WEP, HTTPS, SNMP, SNMPv2, SSH, WPA, WPA-PSK, WPA2-Enterprise,.... Ethernet LAN data rates: 10,100 Mbit/s. Power over Ethernet (PoE). Product colour: White | Vendor Homepage: <https://www.tp-link.com/en/business-networking/ceiling-mount-ap/eap110/v4/#overview> | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No | Cabling technology: 10/100Base-T(X) | Ethernet LAN data rates: 10/100 | Frequency band: 2.4 - 2.4835 | Maximum data transfer rate: 300 | Maximum data transfer rate (2.4 GHz): 300 | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.1x | Quality of Service (QoS) support:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | Rate limiting: Yes | Receiver sensitivity: 300M: -71dBm@10% PER 150M: -75dBm@10% PER 54M: -78dBm@10% PER 11M: -93dBm@8% PER 6M: -92dBm@10% PER 1M: -96dBm@8% PER | Transmitting power (CE): 19 | Transmitting power (FCC): 21 | Virtual LAN features: VLAN mapping | VLAN support: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Wireless isolation: Yes | Access Control List (ACL): Yes | MAC address filtering: Yes | Number of SSID supported: 8 | Security algorithms: 128-bit WEP/152-bit WEP/64-bit WEP/HTTPS/SNMP/SNMPv2/SSH/WPA/WPA2-Enterprise/WPA2-PSK/WPA-PSK | Service Set Identifier (SSID) features: Multiple SSIDs | Syslog: Yes | Web-based management: Yes | Ethernet LAN (RJ-45) ports: 1 | AC input voltage: 24 | Power consumption (typical): 2.8 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | LED indicators: Power | Placement: Ceiling,Wall | Product colour: White | Reset button: Yes | Antenna direction type: Omni-directional | Antenna gain level (max): 4 | Antenna type: Internal | Antennas quantity: 2 | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Depth: 170.5 | Height: 29.7 | Width: 189.5 | Package depth: 268 | Package height: 69 | Package type: Box | Package weight: 720 | Package width: 246 | Cables included: AC | Mounting kit: Yes | PoE adapter included: Yes | Quantity per pack: 1 | Quick start guide: Yes | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Sustainability compliance: Yes | Harmonized System (HS) code: 85176990 | Product Net Weight: 0.7 | Shipping Box Height: 7 | Unit Calculated Volume: 0.004631 | Unit Calculated Weight: 0.81 | Units per Shipping Box: 1 | Series: Omada | Model name: 300Mbps Wireless N Ceiling Mount Access Point

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950