



Switch MERCUSYS MS108GP PoE+ ports 7 MS108GP



Model: MS108GP

Manufacturer: MERCUSYS

EAN: 6957939001209

Product Code: 772775

R1,188

7 PoE+ Ports (65 W Budget) for Network Deployment

All eight ports of the MS108GP are gigabit ports, with seven PoE+ ports (1-7). Each PoE+ port supports a maximum of 30 W and is compliant with the 802.3af/at Powered Devices. The total 65 W PoE power budget* enables a variety of uses, including surveillance for offices, dormitories, and small businesses. IP cameras, access points, IP phones, PCs, video recorders, and more are all completely compatible with it.

No Fuss

No need for electricians; simplify installation and deployment.

Cost-Efficiency

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Getting rid of extra cables and power adapters will save money on infrastructure.

Flexibility

Deployment in complex situations is made possible by more placement possibilities.

Power Management

Improves power usage while intelligently protecting your gadgets from power surges.

IEEE 802.3af/at

PoE ports compliant with the 802.3af/at Powered Devices.

Long-Range up to 250 m with Extend Mode**

Extend Mode** increases PoE transmission distance to 250 m. MS108GP has 7 long-range ports with PoE+. Turn on the Extend Mode and make it ideal for installing surveillance cameras over wide areas.

Traffic Separation

With only one click, isolation mode divides traffic for ports 1-7 to prevent snooping/tampering and isolate broadcast storms for greater protection.

Port Prioritization

Prioritizing the data of specific ports would ensure the high quality of delicate applications, such as voice and video, in crucial business domains.

Plug and Play

MS108GP offers auto-negotiation (10/100/1000 M) and automated MDI/MDIX. There is no additional configuration needed. It is simple to use and saves time and effort.

Durable and Silent

MS108GP's durable metal case allows for efficient heat dissipation, excellent signal interference prevention, equipment stability, and long network life.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Full Gigabit Ports: 8× 10/100/1000 Mbps RJ45 ports
- Two Cables in One: With 7 PoE+ ports, transfers data and power on one single cable
- High Power PoE+: Support PoE Power up to 30 W for each PoE port and 65 W for all PoE ports*
- Long-Range up to 250 m: Increases PoE transmission distance to 250 m by Extend Mode*
- Isolation Mode: One click to divide traffic for specific ports for stability and security
- Compliant with Powered Devices: Works with IEEE 802.3af/at compliant PDs
- Durable Metal Casing: Allows for efficient heat dissipation and long network life
- Plug and Play: Simple to use and saves time and effort

Summary: Mercusys 8-Port Gigabit Desktop Switch with 7-Port PoE+. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 8000 entries. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3x. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://www.mercusys.com/en/product/details/ms108gp> | Perjungimo tipas: Valdomas | Web pagrįstas valdymas: Taip | Eismo klasifikacija: Taip | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 8 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: Gigabit Ethernet (10/100/1000) | Tinklo standartai: IEEE 802.3af/IEEE 802.3at/IEEE 802.3x | 10G parama: Ne | Pilnai abipusis (duplex): Taip | Politika pagrįstas maršrutizavimas: Taip | Pusiau dvipusis: Taip | Auto MDI/MDI-X: Taip | Srauto kontrolės palaikymas: Taip | Adreso lentelės dydis: 8000 | „Store-and-forward“ funkcija: Taip | Stovo montavimas: Ne | Didinimas: Ne | Produkto spalva: Juoda | Korpuso medžiaga: Metalas | Montuojamas ant sienos: Taip | Maitinimo šaltinis: AC | Pridėtas maitinimo šaltinis: Taip | AC įėjimo įtampa: 220 | AC įėjimo dažnis: 50 | Įvesties srovė: 1.31 | Įėjimo įtampa: 53.5 | Energijos suvartojimas: 5.07 | Galios suvartojimas (maks.): 77.33 | Maitinimas per Eternetą (PoE): Taip | Maitinimo per Eternetą (PoE) prievadų skaičius: 7 | Maitinimo per Eternetą plus (PoE+) prievadų skaičius: 1 | Maitinimo per Eternetą (PoE) galia prievadui: 65 | Darbo temperatūros diapazonas (TT): 0 - 40 | Sandėliavimo temperatūros norma (T-T): -40 - 70 | Darbo santykinės drėgmės diapazonas: 10 - 90 | Sandėliavimo santykinis drėgmės diapazonas: 5 - 95 | Šilumos sklaida: 262.922 | Plotis: 171 | Ilgis: 98 | Aukštis: 27 | Pridėti kabeliai: AC | Greitos pradžios vadovas: Taip | Bruto svoris: 0.858 | Neto svoris: 0.5 | Vienetų skaičius vienoje siuntimo dėžėje: 12 | Vieneto plotis: 19 | Shipping Box Height: 28 | Vieneto gylis: 12.5 | Vieneto aukštis: 8.5 | Name: NET SWITCH 8PORT 10/100/1000M/MS108GP MERCUSYS | Model name: 8-Port Gigabit Desktop Switch with 7-Port PoE+

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](mailto:sales@cssi.co.za) | sales@cssi.co.za | +27 (11)541-9950