

Switch TP-LINK TP-LINK LS108G LS108G 8x10Base-T 100Base-TX 1000Base-T LS108G



Model: LS108G

Manufacturer: TP-LINK

EAN: 6935364085452

Product Code: 773015

R1,008

Increase Your Network Speed and Save Energy

Let LiteWave Bring You Lighter Network Life

The TP-Link LiteWave Series Unmanaged Switches provide easy and affordable way to expand your wired network. They are easy to use and reliable. With these plug-and-play switches, you can expand your network connections to multiple devices instantly. With all ports support Auto-MDI/MDIX, there's no need to worry about the type of cable to use.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Go Green with Your Ethernet

The LiteWave Series also supports energy-efficient technology, helping you save power and money. Power consumption automatically adjusts according to link status and cable length, allowing you to expand your network while minimizing your carbon footprint. Save the planet and lower your energy bills — it's a win-win!

Durable Metal Casing

The interior components of LS108G are protected by high-quality metal casing to ensure a long product life. Having passed an array of stringent reliability tests, LS108G delivers switching performance you can depend on. Its compact size makes it ideal for deployment on desktops or work benches.

Use Where You Need, However You Need

The LS108G is fully compatible with networked devices such as computers, printers, webcams, IPTVs. It has a wide range of application scenarios and is suitable for networking in school dormitories, surveillance, homes, and small businesses.

- 10/100/1000Mbps Auto-Negotiation RJ45 port supporting Auto-MDI/MDIX
- Green Ethernet technology saves power
- IEEE 802.3X flow control provides reliable data transfer
- Steel housing, desktop or wall-mounting design
- Support 802.1p/DSCP QoS function
- Plug and play, no configuration needed

Summary: TP-Link 8-Port 10/100/1000Mbps Desktop Network Switch. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 4000 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Power connector: DC-in jack | Vendor Homepage: <https://www.tp-link.com/pe/business-networking/unmanaged-switch/ls108g/#overview> | Quality of Service (QoS) support: Yes | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 8 | Power connector: DC-in jack | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Flow control support: Yes | Networking standards: IEEE 802.1p/IEEE 802.3ab/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x | Forwarding

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

rate: 11.9 | Jumbo frames: 16000 | Jumbo frames support: Yes | MAC address table: 4000 | Packet buffer memory: 1.5 | Switching capacity: 16 | LED indicators: Activity/LAN/Power | Product colour: Blue | Rack mounting: No | Input current: 0.6 | Input voltage: 5 | Power consumption (max): 3.7 | Power source: DC | Power supply included: Yes | Power over Ethernet (PoE): No | Heat dissipation: 12.617 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -40 - 70 | Depth: 99 | Height: 25 | Width: 158 | Quick start guide: Yes | Package depth: 191 | Package height: 92 | Package weight: 470 | Package width: 130 | Certification: CE, FCC, RoHS | Harmonized System (HS) code: 85176990 | Product Net Weight: 0.4 | Shipping Box Height: 40 | Unit Calculated Volume: 0.002733 | Unit Calculated Weight: 0.539 | Units per Pallet: 0 | Units per Shipping Box: 36 | Series: TP-LINK LS108G | Model name: LS108G

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950