



D-Link 12-Port L2 Industrial Smart Managed Switch with 10 x 1GBaseT(X) (8 PoE 240W) & 2 x SFP



Model: DIS-200G-12PS

Manufacturer: D-LINK

EAN: 790069433504

Product Code: 801909

R15,129

Smart Management

Featuring management interfaces, including an industry-standard CLI, and Web-based UI, the DIS-200G Serie is easy to manage and provides the controls to help protect and shape your network.

Gigabit Connectivity with PoE and SFP ports

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Designed with 8 x 10/100/1000Base-T PoE ports, 2 x 10/100/1000Base-T ports, and 2 x SFP ports to suit a range of devices and network layouts.

Officially Certified

Certifications for vibration, shock, free-fall, electromagnetic, and high-capacity 6 kV surge protection on all copper ports to maximise network uptime in harsh deployment environments.

Withstands Extreme Temperatures

Operates effortlessly in a range of industrial and harsh environments in temperatures from -40°C to +65°C.

PoE Support

With its 240 W PoE+ power budget¹, it's been designed to supply data and PoE power to compliant devices, which removes the need for unnecessary plugs and cables and reduces deployment time and effort.

High Redundancy and Reliability

ERPS quick failover recovery for ring topologies that ensures minimal downtime and avoids any loss of data in mission-critical deployment settings.

Strong Build

The tough housing has been created to keep your network protected and reliably rugged.

Enhanced IP Surveillance

Supports Auto-Surveillance VLAN (ASV), automatically detecting surveillance devices and putting them into a dedicated surveillance VLAN, increasing security of surveillance data, and giving the traffic a higher priority.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Fanless Design

With no moving parts inside to reduce downtime and maintenance call outs, the rugged housing has been optimised for the transfer of heat.

Fast Deployment

For instant installation it features a snap-to-DIN-rail clip, and also supports wall mounting.

Discrete Size

Small but mighty. To make the most of cabinet space, it measures: 48 x 210 x 171.2 mm.