



Ernitec 0070- 24122-POE computer monitor 55.9 cm (22") 1920 x 1080 pixels Full HD LED Black



Model: 0070-24122-POE

Manufacturer: ERNITEC

EAN: 5715063081341

Product Code: 81497

R3,327

Industrial level DID LCD panel

- Suitable for extensive 24/7 continuous operating hours
- Physical resolution of 1920×1080
- 5ms fast response time, no image ghosting.
- Adapt newest 3D digital filtering and 3D digital noise

reduction technology

- Picture fast response
- 178° wide viewing angle
- Ensure that the image display is not deformed

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- High fidelity digital processing, brilliant and vivid video
- Built-in speaker
- Menu with convenient controller
- Power: Supports transfer of 100m power from PoE switch, POE injector or even from a free POE port on the NVR to

monitor directly, Green Power Devices

- POE type - IEEE 802.3af/at/bt

PoE eliminates the need for separate power cables.

A single Ethernet cable carries both data and power, streamlining installation and reducing clutter.

Cost-Effective:

PoE reduces infrastructure costs by minimizing the number of cables and power outlets required.

No need for additional power supplies or electrical work.

Flexibility and Scalability:

Easily relocate or expand surveillance systems without rewiring.

Add new devices (monitors, cameras, etc.) without major modifications.

Remote Power Management:

Monitor and control power remotely.

Reboot devices or adjust power settings from a central location.

Reliable Performance:

PoE monitors receive consistent power supply, reducing downtime.

Uninterrupted operation even during power outages (with backup power solutions).

Safety and Efficiency:

Low-voltage power delivery minimizes electrical hazards.

Energy-efficient operation.

Integration with Network Infrastructure:

Seamlessly integrate with existing Ethernet networks.

Compatible with PoE switches and routers.

Clean Aesthetics:

Fewer visible cables enhance the overall appearance of the surveillance setup.

VESA size: 100x100