# D-Link DMS-3130-30PS Managed L3 10G Ethernet (100/1000/10000) Power over Ethernet (PoE) Black

Model: DMS-3130-30PS/E

Manufacturer: D-LINK

Product Code: 841421

## R80,727

Produktbeschreibung Die DMS-3130 Serie umfasst Layer-3 stapelbare Multi-Gigabit Managed Switches, die speziell für den sicheren Anschluss von Endnutzern in Unternehmens- oder Metro-Ethernet-Zugangsnetzwerken entwickelt wurden. Diese Switches unterstützen Multicasting sowie erweiterte Sicherheitsfunktionen und sind somit die ideale Lösung für Multi-Gigabit-Zugangsnetzwerke. Jedes Modell ist mit zwei 10GBASE-T Ports und vier 10G/25G SFP28 Ports ausgestattet, die sowohl Vielseitigkeit als auch hohe Geschwindigkeit bieten. Dadurch eignen sich die DMS-3130 Switches perfekt für anspruchsvolle Netzwerkanwendungen, bei denen Leistung, Sicherheit und Skalierbarkeit im Vordergrund stehen.Art.-Nr.: 100103510 Typ: Switch | EAN: 0790069467172 | Hersteller-Nr.: DMS-3130-30PS/E | Bauform: Rack | Einsatzbereich: Business |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Anschlüsse: 26x (davon: 16x 100/1000/2500, 8x 100/1000/2500/5000, 2x 1000/2500/5000/10000, 1x Konsolenport) | Routing & Switching: Layer 3 Routing, Layer 2 Switching | Stromversorgung: Stromverbrauch inkl. PoE-Geräte: 1211.5 W, PoE Gesamt-Budget: 740 W, max. PoE Versorgung pro Port: 60 W | Feature: MAC Address Table: 32K (32,768) entries | Flow Control | 802.3x Flow Control | HOL Blocking Prevention | Jumbo Frames up to 9 Kbytes | 802.1AX/802.3ad Link Aggregation | Max. 32 groups per device, 8 ports per group | Spanning Tree Protocols | 802.1D STP | 802.1w RSTP | 802.1s MSTP | BPDU Filtering | Root Guard | Loop Guard | Loopback Detection | Port Mirroring | Supports One-to-One, Many-to-One | Supports Mirroring for both Tx/Rx | Supports 4 mirroring groups | Flow mirroring | Supports Mirroring for Tx/Rx | VLAN Mirroring | RSPAN | L2 Protocol Tunneling | Ethernet Ring Protection Switching (ERPS) v1/v2 || IGMP Snooping | IGMP v1/v2/v3 Snooping | Supports 1024 IGMP groups | IGMP Snooping Fast Leave | Supports 128 static IGMP groups | Per VLAN IGMP Snooping | Data Driven Learning | IGMP Snooping Querier | IGMP Authentication | IGMP Accounting | Report Suppression | MLD Snooping | MLD v1/v2 Snooping | Support 1024 MLD Groups | Host-based MLD Snooping Fast Leave | Supports 64 static MLD groups | MLD Snooping Querier | Per VLAN MLD Snooping | MLD Proxy Reporting | Weitere Informationen: 1x 10/100/1000BASE-T RJ-45 port for out-of-band IP management | Stacking Ports: 4 | Abmessungen: Breite: 440 mm x Höhe: 44 mm x Tiefe/Länge: 470 mm | Gewicht: 6,5 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950