Intel Xeon gold 6230N, processor - Tray-Version

Model: CD8069504283604

Manufacturer: INTEL

Product Code: 841596

R43,690

Produktbeschreibung Der für Server und Workstations konzipierte Intel® Xeon® Gold 6230N Prozessor ist eine native 20-Kern-CPU auf Basis der "Cascade Lake"-Architektur. Der Xeon® Gold 6230N läuft mit einem CPU-Takt von 2,30 GHz (Turbo-Modus bis 3,90 GHz) und besitzt einen L3-Cache von 28 MB. Diverse Verbesserungen der Architektur sorgen für eine gesteigerte Leistung und eine Leistungssteigerung in Anwendungen selbst bei nicht optimiertem Code. Der integrierte Speichercontroller unterstützt DDR4-RAM bis 2933 MHz.Art.-Nr.: 1542026 Typ: Server | Hersteller-Nr.: CD8069504283604 | CPU-Typ: Xeon Gold | Bauform: FC-LGA4 | Kern: Xeon Gold 6xxx (Purley) | Cache: Level 3: 28672 KB | Lüfter: Kein Lüfter im Lieferumfang enthalten | CPUs in Multiprozessorsystem: 4 | Speicher-Controller: ECC | Grafik: ohne CPU-Grafik | Stromverbrauch (TDP): 125 Watt | Befehlssätze: Intel® Deep Learning Boost (Intel® DL Boost), Intel® Speed Select Technology – Grundtaktfrequenz, Intel® Resource Director Technology (Intel® RDT), Intel® Speed Shift Technology, Intel® Turbo Boost Technik 2.0, Intel® vPro™ Plattformqualifizierung, Intel® Hyper-Threading-Technik, Intel® Virtualisierungstechnik (VT-x), Intel® Directed-I/O-Virtualisierungstechnik (VT-d), Intel® VT-x mit Extended Page Tables (EPT), Intel® TSX-NI, Intel® 64, Intel® AVX-512, Anzahl der AVX-512 FMA-Einheiten = 2, Erweiterte Intel SpeedStep® Technologie,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Intel® Volume Management Device (VMD), Intel® AES New Instructions, Intel® Trusted Execution Technik, Execute Disable Bit, Intel® Run Sure Technik, MBE (Mode-based Execute Control, modusbasierte Ausführungssteuerung) | Weitere Informationen: Max. Speichergröße (abhängig vom Speichertyp): 1 TB | persistenter Intel® Optane™ DC Speicher wird unterstützt | Hinweis: Tray-Version | Gewicht: 46 Gramm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950