CISCO C9300L 24-port PoE 4x10G Uplink 715WAC PS Meraki Persona

Model: C9300L-24P-4X-M

Manufacturer: CISCO

Product Code: 873488

R150,412

The Cisco Meraki Catalyst 9300L-24P-4X switch is designed to meet the demands of modern networks, offering a blend of performance, security, and manageability. With 24 RJ-45 ports for 1000Base-T connections and 4 SFP+ ports for 1/10GBase-X uplinks, it provides the flexibility needed for various networking requirements. Security is a priority, featuring RADIUS authentication and a host of security measures to protect network integrity. Performance-wise, it delivers with a 128 Gbps switching capacity and up to 95.23 Mpps forwarding rate, ensuring smooth data flow even under heavy loads. Additionally, its support for remote management protocols like DHCP, SNMP, and Syslog allows for seamless network administration. The inclusion of power redundancy through its hot-plug internal power supply ensures reliability and uninterrupted service, making it an ideal solution for businesses looking to bolster their network infrastructure.

Product Description: Cisco Meraki Catalyst 9300L-24P-4X - switch - 24 ports - Managed - rack-mountable | Device Type: Switch - 24 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 (PoE+) + 4 x 1/10 Gigabit

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(uplink) | Power Over Ethernet (PoE): PoE+ | PoE Budget: 505 W | Performance: Switching capacity: 128 Gbps Forwarding rate: 95.23 Mpps Forwarding rate with stacking: 333.33 Mpps Stacking bandwidth: 448 Gbps | Capacity: Priority queues: 8 Maximum number of VLANs: 4094 Active VLANs: 1000 Link aggregation ports: 8 | MAC Address Table Size: 32000 entries | Routing Protocol: Static IP routing, STP, OSPFv2, VRRP | Remote Management Protocol: SNMP, Syslog, DHCP | Features: ACL support, ZTP, firmware upgradable, push notification, QoS, DSCP to CoS mapping, VLAN support, VLAN trunking, BPDU Guard, Root Guard, Loop Guard, UDLD, Broadcast Storm Control, CDP, port mirroring, IGMP snooping, Multicast filtering function, Multicast routing, DHCP server, DHCP relay, RBAC, 802.1x authentication, MAB, Port Security, DHCP snooping, DAI, 3 fans | Compliant Standards: IEEE 802.1p, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3ad (LACP), IEEE 802.1x, IEEE 802.3af, IEEE 802.3at | Power: AC | Power Redundancy: Yes | Dimensions (WxDxH): 44.5 cm x 44.9 cm x 4.4 cm | Weight: 7.35 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950