CISCO C9300L 48-port Full PoE 4x10G Uplink 1100WAC PS Meraki Persona

Model: C9300L-48PF-4X-M

Manufacturer: CISCO

Product Code: 873491

R245,713

The Cisco Meraki Catalyst 9300L-48PF-4X switch is designed to meet the demands of modern network environments, offering a blend of performance, security, and reliability. With 48 PoE+ ports and 4 SFP+ uplink connections, it provides the necessary infrastructure to support a wide range of devices, from access points to IP cameras, without compromising on speed or connectivity. The switch's performance is highlighted by its 176 Gbps switching capacity and 130.95 Mpps forwarding rate, ensuring efficient data processing and traffic management across the network. Security is a priority, with features like 802.1x authentication, ACL support, and Dynamic ARP Inspection safeguarding against potential threats. Reliability is further assured with an MTBF of 298,880 hours and efficient cooling provided by 3 fans, making it a dependable choice for critical network operations. Additionally, its 890 W PoE budget and power redundancy options ensure that connected devices remain operational, making it an ideal solution for businesses looking to enhance their network infrastructure.

Product Description: Cisco Meraki Catalyst 9300L-48PF-4X - switch - 48 ports - Managed - rack-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

mountable | Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 10/100/1000 (PoE+) + 4 x 1/10 Gigabit (uplink) | Power Over Ethernet (PoE): PoE+ | PoE Budget: 890 W | Performance: Switching capacity: 176 Gbps Forwarding rate: 130.95 Mpps Forwarding rate with stacking: 369.05 Mpps Stacking bandwidth: 496 Gbps | Capacity: Priority queues: 8 Maximum number of VLANs: 4094 Active VLANs: 1000 Link aggregation ports: 8 | MAC Address Table Size: 32000 entries | Routing Protocol: Static IP routing, STP, OSPFv2, VRRP | Remote Management Protocol: SNMP, Syslog, DHCP | Features: ACL support, ZTP, firmware upgradable, push notification, QoS, DSCP to CoS mapping, VLAN support, VLAN trunking, BPDU Guard, Root Guard, Loop Guard, UDLD, Broadcast Storm Control, CDP, port mirroring, IGMP snooping, Multicast filtering function, Multicast routing, DHCP server, DHCP relay, RBAC, 802.1x authentication, MAB, Port Security, DHCP snooping, DAI, 3 fans | Compliant Standards: IEEE 802.1p, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3ad (LACP), IEEE 802.1x, IEEE 802.3af, IEEE 802.3at | Power: AC | Power Redundancy: Yes | Dimensions (WxDxH): 44.5 cm x 48.8 cm x 4.4 cm | Weight: 7.03 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950