



## **CISCO C9300L 48-port data 4x10G Uplink 350WAC PS Meraki Persona**



Model: C9300L-48T-4X-M

Manufacturer: CISCO

EAN: 810087206222

Product Code: 873492

## **R186,321**

The Cisco Meraki Catalyst 9300L-48T-4X switch is designed to meet the demands of modern network environments, offering a blend of performance, security, and manageability. With its 48 1000Base-T ports and 4 1/10GBase-X uplink ports, this device provides ample connectivity for a variety of devices and network configurations. Security is a priority, with features like RADIUS authentication and Access Control List (ACL) support ensuring a secure network environment. Performance is high, thanks to a switching capacity of 176 Gbps and a forwarding rate of 130.95 Mpps, making it suitable for handling large volumes of data with ease. Additionally, the switch's stackable design allows for scalability, accommodating growing network needs. With an MTBF of 380,080 hours and support for advanced management protocols like SNMP and Syslog, the Cisco Meraki Catalyst 9300L-48T-4X is a reliable and efficient solution for any network.

Product Description: Cisco Meraki Catalyst 9300L-48T-4X - switch - 48 ports - Managed - rack-mountable | Device Type: Switch - 48 ports - L3 - Managed - stackable | Enclosure Type: Rack-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

mountable 1U | Subtype: Gigabit Ethernet | Ports: 48 x 1000Base-T + 4 x 1/10 Gigabit (uplink) | Performance: Switching capacity: 176 Gbps Forwarding rate: 130.95 Mpps Forwarding rate with stacking: 369.05 Mpps Stacking bandwidth: 496 Gbps | Capacity: Priority queues: 8 Maximum number of VLANs: 4094 Active VLANs: 1000 Link aggregation ports: 8 | MAC Address Table Size: 32000 entries | Routing Protocol: Static IP routing, STP, OSPFv2, VRRP | Remote Management Protocol: SNMP, Syslog, DHCP | Features: ACL support, ZTP, firmware upgradable, push notification, QoS, DSCP to CoS mapping, VLAN support, VLAN trunking, BPDU Guard, Root Guard, Loop Guard, UDLD, Broadcast Storm Control, CDP, port mirroring, IGMP snooping, Multicast filtering function, Multicast routing, DHCP server, DHCP relay, RBAC, 802.1x authentication, MAB, Port Security, DHCP snooping, DAI, 3 fans | Compliant Standards: IEEE 802.1p, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3ad (LACP), IEEE 802.1x | Power: AC | Power Redundancy: Yes | Dimensions (WxDxH): 44.5 cm x 44.9 cm x 4.4 cm | Weight: 7 kg | Manufacturer Warranty: Limited lifetime warranty

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950