

## TP-Link Omada 16-Port Gigabit Smart Switch with 2 SFP Slots



Model: TL-SG2218

Manufacturer: TP-LINK

EAN: 1210002611824

Product Code: 950084

## R3,949

Certification: CE, FCC, RoHS | Web-based management: Yes | Product colour: Black | Number of static routes: 32 | MAC address table: 8000 entries | GARP VLAN Registration Protocol (GVRP): Yes | Operating relative humidity (H-H): 10 - 90% | DHCP features: DHCP client | DHCP features: DHCP relay | Packet buffer memory: 4.1 MB | Port mirroring: Yes | DHCP features: DHCPv6 client | Basic switching RJ-45 Ethernet ports quantity: 16 | DHCP features: DHCP server | DHCP features: DHCP snooping | Package height: 80 mm | Form factor: 1U | Networking standards: IEEE 802.3z | VLAN support: Yes | Networking standards: IEEE 802.3i | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Multicast support: Yes | AC input frequency: 50/60 Hz | Power over Ethernet (PoE): No | Width: 440 mm | DHCP features: DHCPv6 snooping | Storage relative humidity (H-H): 5 - 90% | Virtual LAN features: Private VLAN | Rack mounting: Yes | Package width: 250 mm | Networking standards: IEEE 802.3ab | IGMP snooping: Yes | Access Control List (ACL): Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | ARP inspection: Yes | Switch layer: L2/L2+ | System event log: Yes | BPDU filtering/protection: Yes | Harmonized System (HS) code: 85176990 | Operating temperature (T-T): 0 - 40 °C | Depth: 180 mm | Virtual LAN features: Tagged VLAN | Virtual LAN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

features: Voice VLAN | Networking standards: IEEE 802.3u | MIB support: Yes | Rate limiting: Yes | Power source: AC | SFP module slots quantity: 2 | Loop protection: Yes | Heat dissipation: 41.97 BTU/h | LED indicators: Yes | AC input voltage: 100 - 240 V | Virtual LAN features: Protocol-based VLAN | Management protocols: SNMPv1/v2c/v3, SNTP | Static route: Yes | Power supply included: Yes | Number of IP interfaces: 16 | Switch type: Managed | 10G support: No | Storage temperature (T-T): - 40 - 70 °C | Quality of Service (QoS) support: Yes | Virtual LAN features: Port-based VLAN | SSH/SSL support: Yes | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Cloud-managed: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Power consumption (max): 12.3 W | Package weight: 2.45 kg | Switching capacity: 36 Gbit/s | Height: 44 mm | Forwarding rate: 26.8 Mpps | Cables included: AC | Cables included: LAN (RJ-45) | Jumbo frames support: Yes | Quick start guide: Yes | Store-and-forward: Yes | Number of VLANs: 4000 | Package depth: 528 mm | Flow control support: Yes | Fanless: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950