

Switch UBIQUITI Type L3 PoE ports 24 600 Watts USW-PRO- HD-24-POE



Model: USW-PRO-HD-24-POE

Manufacturer: UBIQUITI

EAN: 810084696606

Product Code: 950541

R22,180

Professional-grade, Layer 3 Etherlighting™ switch with (2) 10 GbE PoE++, (22) 2.5 GbE PoE++, and (4) 10G SFP+ ports.

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network*
- (22) 2.5 GbE, (2) 10 GbE PoE++ ports
- (4) 10G SFP+ ports
- DC power backup ready**
- 600W total PoE availability

Summary: Ubiquiti UniFi Pro HD 24 PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

quantity: 22. MAC address table: 32000 entries, Switching capacity: 230 Gbit/s. Networking standards: IEEE 802.1x. Power connector: AC/DC. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://eu.store.ui.com/eu/en/products/usw-pro-hd-24-poe> | Quality of Service (QoS) support: Yes | Switch layer: L2/L3 | Switch type: Managed | 10G Ethernet (copper) ports quantity: 2 | 2.5G Ethernet (copper) ports quantity: 22 | Basic switching RJ-45 Ethernet ports quantity: 22 | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Power connector: AC/DC | SFP+ module slots quantity: 4 | 10G support: Yes | Broadcast storm control: Yes | Flow control support: Yes | IPv4 routes: 12000 | Networking standards: IEEE 802.1x | Number of VLANs: 1000 | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Voice VLAN | VLAN support: Yes | Forwarding rate: 171 | Jumbo frames support: Yes | MAC address table: 32000 | Packet buffer memory: 2 | Static route: Yes | Switching capacity: 230 | Throughput: 115 | DHCP features: DHCP guarding/DHCP relay/DHCP server/DHCP snooping | IGMP snooping: Yes | Loop protection: Yes | Multicast support: Yes | Display type: LCM | Form factor: 1U | Housing material: SGCC | LED indicators: Link/Speed/Status | Product colour: Grey | Rack mounting: Yes | Reset button: Yes | Stackable: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 60 | Power source: AC/DC/PoE | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 15.4 | Power over Ethernet 4PPoE (PoE++) ports quantity: 24 | Total Power over Ethernet (PoE) budget: 600 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 400 | Height: 44 | Weight: 6200 | Width: 442.4 | Cables included: Power | Rack mount kit: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC) | Product Net Weight: 6.3 | Shipping Box Height: 55 | Unit Calculated Volume: 0.04008 | Unit Calculated Weight: 8.38 | Units per Pallet: 0 | Units per Shipping Box: 2 | Model: USW-PRO-HD-24-POE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950