

Switch UBIQUITI Flex Mini 2.5G Type L2 5x2.5GbE USW- FLEX-2.5G-5



Model: USW-FLEX-2.5G-5

Manufacturer: UBIQUITI

EAN: 810084696040

Product Code: 951632

R1,748

Compact, 5-port 2.5G switch that can be powered with PoE or a USB-C adapter.

- Optional powering with included 5V, 1A USB-C adapter
- Ethernet In-Band
- Certifications CE, FCC, IC

Summary: Ubiquiti UniFi Flex Mini 2.5G. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 5. Switching capacity: 25 Gbit/s. DC input voltage: 5 V. Power connector: USB. Power over Ethernet (PoE). Form factor: Desktop | Vendor Homepage: <https://eu.store.ui.com/eu/en/products/usw-flex-2-5g-5> | Switch type: Managed | 2.5G Ethernet (copper) ports quantity: 5 | Basic switching RJ-45 Ethernet ports quantity: 5 | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

connector: USB | USB Type-C ports quantity: 1 | 10G support: No | Broadcast storm control: Yes | Copper ethernet cabling technology: 2.5GBASE-T | Flow control support: Yes | Port mirroring: Yes | Rate limiting: Yes | Forwarding rate: 18.6 | Jumbo frames support: Yes | Switching capacity: 25 | Throughput: 12.5 | Multicast support: Yes | Form factor: Desktop | Housing material: Polycarbonate (PC) | LED indicators: Activity/Power/Progress | Product colour: White | Reset button: Yes | Minimum system requirements: UniFi Network Version 8.4.62 and later | DC input voltage: 5 | Input current: 1 | Power consumption (max): 5 | Power plug type: Type A | Power source: AC/DC/PoE | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 6.4 | Power over Ethernet (PoE) voltage: 57 | Networking features: STP / RSTP with priorities and port-level disable, Egress rate limit | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): - 20 - 45 | Depth: 90 | Height: 21.2 | Weight: 206 | Width: 117.1 | AC adapter included: Yes | Certification: CE, FCC, IC | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC) | Product Net Weight: 0.206 | Shipping Box Height: 19.8 | Unit Calculated Volume: 0.001429 | Unit Calculated Weight: 0.456 | Units per Shipping Box: 18 | Model: USW-FLEX-2.5G-5 | Model name: Flex Mini 2.5G

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950