



Access Point UBIQUITI 2402 Mbit/s 1xLAN ports U6+



Model: U6+

Manufacturer: UBIQUITI

EAN: 810084691090

Product Code: 952897

R3,064

WRL ACCESS POINT/U6+ UBIQUITI

- 1,500 ft² coverage
- 300+ connected devices
- WiFi6 (2x2 MIMO)
- Powered using PoE

Summary: Ubiquiti U6+. 2.4 GHz, 5 GHz, Maximum data transfer rate: 2402 Mbit/s. Security algorithms: WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA3-Enterprise. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 9 W | Vendor Homepage: <https://eu.store.ui.com/eu/en/collections/unifi-wifi-flagship-compact/products/u6-plus> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Maximum data transfer rate: 2402 | Maximum data transfer rate (2.4 GHz): 573.5 | Maximum data transfer rate (5 GHz): 2402 | Maximum indoor range: 139.35 | MIMO: Yes | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11b/IEEE 802.11g/IEEE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

802.11n/IEEE 802.1Q | Number of users: 300 | Quality of Service (QoS) support: Yes | Transmitting power: 23 | VLAN support: Yes | Security algorithms: WPA2-Enterprise/WPA3-Enterprise/WPA-Enterprise/WPA-PSK | Ethernet LAN (RJ-45) ports: 1 | Internal RJ-45 ports quantity: 1 | DC voltage range: 44 - 57 | Power consumption (max): 9 | Power over Ethernet (PoE): Yes | Housing material: Aluminium, Polycarbonate (PC) | LED indicators: Yes | Placement: Ceiling | Product colour: White | Reset button: Yes | Antenna gain level (max): 5.4 | Antenna type: Internal | Certification: IC | Compliance certificates: CE/Federal Communications Commission (FCC) | Depth: 160 | Height: 33 | Weight: 338 | Width: 160 | Mounting kit: Yes | Quantity per pack: 1 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -30 - 60 | Product Net Weight: 0.413 | Shipping Box Height: 42 | Unit Calculated Volume: 0.002911 | Unit Calculated Weight: 0.65 | Units per Pallet: 0 | Units per Shipping Box: 20 | Model name: U6+

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950