

TP-Link 16-Port Gigabit Desktop Network Switch



Model: TL-SG116

Manufacturer: TP-LINK

EAN: 1210002616980

Product Code: 953235

R1,854

Basic switching RJ-45 Ethernet ports quantity: 16 | Copper ethernet cabling technology: 10BASE-T | Packet buffer memory: 4.1 MB | Port mirroring: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | IGMP snooping: Yes | Full duplex: Yes | Harmonized System (HS) code: 85176990 | Broadcast storm control: Yes | Jumbo frames support: Yes | DC input voltage: 9 V | Gigabit Ethernet (copper) ports quantity: 16 | Power over Ethernet (PoE): No | Width: 286 mm | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | VLAN support: Yes | Power supply included: Yes | Input current: 0.6 A | Loop protection: Yes | Copper ethernet cabling technology: 1000BASE-T | 10G support: No | Number of VLANs: 32 | Cable length detection: Yes | Flow control support: Yes | Link aggregation: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Store-and-forward: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 90% | Cable types supported: Cat4 | Auto MDI/MDI-X: Yes | Rack mounting: No | Cable types supported: Cat5 | Cable types supported: Cat5e | LED indicators: Yes | Height: 25.4 mm | Heat dissipation: 31.68 BTU/h | Number of queues: 4 | Switch type: Unmanaged | Copper ethernet cabling technology: 100BASE-TX | Cables included: AC | Cable types supported: Cat3 | Wall mountable: Yes | Rate limiting: Yes | Cable types

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: Cat6 | Quick start guide: Yes | Switching capacity: 32 Gbit/s | Housing material: Metal | Virtual LAN features: Protocol-based VLAN | Forwarding rate: 23.81 Mpps | Jumbo frames: 9000 | Virtual LAN features: Tagged VLAN | Depth: 111.7 mm | Power consumption (max): 9.3 W | AC input frequency: 50 Hz | Product colour: Black | AC input voltage: 220 V | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950