

Cudy LT400 wireless router Fast Ethernet Single-band (2.4 GHz) 4G White



Model: LT400 OUTDOOR_EU

Manufacturer: CUDY

EAN: 6971690792916

Product Code: 954023

R1,965

VPN support: PPTP/L2TP/OpenVPN/WireGuard/IPSec/Zerotier | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to water or moisture. | PoE injector included: Yes | Warnings: Do not expose the device to extreme temperatures. | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows 10 Education | Package weight: 794 g | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows Vista Ultimate x64 | Weight: 420 g | Storage temperature (T-T): -40 - 70 °C | Power source type: PoE | Package width: 324 mm | Reset button: Yes | Wake-on-LAN ready: Yes | Security algorithms: WPA | Windows operating systems supported: Windows Vista Home Premium | Security algorithms: WPA2 | MAC address filtering: Yes | Security algorithms: WPA3 | Filtering: Yes | Windows operating systems supported: Windows Vista Home

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Basic | Storage relative humidity (H-H): 5 - 95% | Product colour: White | Modulation: 64-QAM | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | DHCP client: Yes | Operating temperature (T-T): -20 - 60 °C | Ethernet LAN (RJ-45) ports: 1 | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows Vista Home Premium x64 | Operating relative humidity (H-H): 0 - 100% | Ethernet LAN data rates: 100 | Power over Ethernet (PoE): Yes | AC input frequency: 50/60 Hz | Ethernet LAN data rates: 10 | Mounting kit: Yes | Windows operating systems supported: Windows XP Professional x64 | Windows operating systems supported: Windows 10 Pro x64 | Windows operating systems supported: Windows 8 Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | AC input voltage: 100 - 240 V | Windows operating systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 IoT Enterprise | Windows operating systems supported: Windows 7 Professional x64 | Windows operating systems supported: Windows 11 Enterprise | Windows operating systems supported: Windows 10 Enterprise x64 | Windows operating systems supported: Windows 10 x64 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | LED indicators: WLAN | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows XP Professional | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows 10 Education x64 | Windows operating systems supported: Windows XP Home x64 | Antenna gain level (max): 5 dBi | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: Windows Vista | Windows operating systems supported: Windows 7 x64 | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows 11 | Depth: 100 mm | USB port: No | DMZ support: Yes | Port forwarding: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Dynamic DNS (DDNS): Yes | Ethernet LAN: Yes | Flash memory: 8 MB | Port triggering: Yes | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | IGMP snooping: Yes | Width: 240 mm | Firewall: Yes | 4G standard: LTE-TDD & LTE-FDD | WAN connection type: RJ-45 | Ethernet LAN interface type: Fast Ethernet | Wall mountable: Yes | International Protection (IP) code: IP65 | Height: 53.7 mm | Package height: 86 mm | Wi-Fi band: Single-band (2.4 GHz) | Output voltage: 24 V | 3G standards: WCDMA | Detachable antenna(s): Yes | Mobile network generation: 4G | Ethernet WAN: Yes | Cables included: LAN (RJ-45) | Mac operating systems supported: Yes | 2G standards: GSM | SIM card type: NanoSIM | Dual SIM support: No | Supported network protocols: IPv4 / IPv6 | 2G standards: Edge | SIM card slot: Yes | Wi-Fi standards: 802.11g | URL filtering: Yes | IP address filtering: Yes | Product type: Desktop/pole router | Package depth: 107 mm | Internal memory: 64 MB | Quick installation guide: Yes | Universal Plug and Play (UPnP): Yes | Linux operating systems supported: Yes | WLAN data transfer rate (max): 300 Mbit/s | Antennas quantity: 4 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: 802.11b | Number of guest networks (2.4 GHz): 1 | Antenna design: Internal & external

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950