

TP-Link TL- MR100 wireless router Fast Ethernet Single- band (2.4 GHz) 4G Black



Model: TL-MR100

Manufacturer: TP-LINK

EAN: 1210002609258

Product Code: 960606

R1,722

Receiver sensitivity: 11g 54M: -74dBm 11n HT20: -71dBm 11n HT40: -67dBm | Certification: CE, RoHS | Ethernet WAN: Yes | Harmonized System (HS) code: 85176990 | Memory card slot(s): No | Wi-Fi Multimedia (WMM)/(WME): Yes | Linux operating systems supported: Yes | Output voltage: 9 V | Wi-Fi standards: 802.11g | 3G standards: HSPA | USB port: No | Wi-Fi band: Single-band (2.4 GHz) | Ethernet LAN interface type: Fast Ethernet | Wi-Fi standards: 802.11b | 4G bands supported: 2100 | 4G bands supported: 800 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Cabling technology: 10/100Base-T(X) | 4G bands supported: 2600 | 4G bands supported: 2500 MHz | Output current: 0.85 A | 3G standards: UMTS | 3G bands supported: 850 | 4G standard: LTE-TDD & LTE-FDD | Width: 154 mm | Universal Plug and Play (UPnP): Yes | WAN connection type: RJ-45 | WLAN data transfer rate (max): 300 Mbit/s | Antennas quantity: 2 | Height: 36 mm | Product type: Tabletop router | Quick installation guide: Yes | 4G bands supported: 900 | Package height: 66 mm | Top Wi-Fi standard: Wi-Fi 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(802.11n) | Port forwarding: Yes | DHCP server: Yes | On/off switch: Yes | 3G bands supported: 900 | Guest access: Yes | 3G/4G USB modem compatibility: No | Dynamic DNS (DDNS): Yes | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Ethernet LAN: Yes | SIM card slot: Yes | Depth: 114 mm | IP address filtering: Yes | Supported network protocols: IPv4, IPv6 | Mobile network generation: 4G | 4G bands supported: 1800 | 3G bands supported: 2100 | DMZ support: Yes | 4G bands supported: 1900 | WPS push button: Yes | Firewall: Yes | Port triggering: Yes | 4G bands supported: 2300 | SIM card type: MicroSIM | Equivalent Isotropically Radiated Power (EIRP) (@IEEE 802.11n): 20 dBmW | Operating temperature (T-T): 0 - 40 °C | Package weight: 480 g | Operating relative humidity (H-H): 10 - 90% | DHCP client: Yes | Storage temperature (T-T): -40 - 70 °C | Ethernet LAN data rates: 100 | Antenna connector type: N-type | 4G: Yes | AC adapter included: Yes | Reset button: Yes | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Package depth: 161 mm | Product colour: Black | Stateful Packet Inspection (SPI): Yes | Ethernet LAN (RJ-45) ports: 2 | Mac operating systems supported: Yes | Power source type: DC | MAC address filtering: Yes | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA | Networking standards: IEEE 802.11b | DC-in jack: Yes | 3G: Yes | Weight: 150 g | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: 128-bit WEP | Security algorithms: WPA2-PSK | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows NT | Windows operating systems supported: Windows XP | Cables included: LAN (RJ-45) | Package width: 293 mm | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Windows operating systems supported: Windows 7 | Quality of Service (QoS) support: Yes | Wireless statistics: Yes | Wireless radio: Yes | Antenna design: External | Schedule access: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950