

TP-Link 5-Port Gigabit Easy Smart PoE Switch with 4- Port PoE+



Model: TL-SG105PE

Manufacturer: TP-LINK

EAN: 1210002616850

Product Code: 960658

R1,432

Certification: FCC, CE, RoHS | Loop protection: Yes | Harmonized System (HS) code: 85176990 |
Switching capacity: 10 Gbit/s | Fanless: Yes | Power source: DC | MAC address table: 2000 entries |
Port mirroring: Yes | Packet buffer memory: 1 MB | Rate limiting: Yes | Width: 99.8 mm | Rack
mounting: No | IGMP snooping: Yes | Cable types supported: Cat3 | Cable types supported: Cat4 |
Cable types supported: Cat5 | Cable types supported: Cat5e | Auto-negotiation: Yes | Power supply
included: Yes | Cable types supported: Cat6 | Auto MDI/MDI-X: Yes | Heat dissipation: 256.3 BTU/h |
Switch type: Managed | Gigabit Ethernet (copper) ports quantity: 5 | Store-and-forward: Yes | Jumbo
frames support: Yes | Jumbo frames: 16000 | Broadcast storm control: Yes | Height: 25 mm | Total
Power over Ethernet (PoE) budget: 65 W | Power over Ethernet plus (PoE+) ports quantity: 4 | Link
aggregation: Yes | Forwarding rate: 7.44 Mpps | Package height: 121 mm | Number of queues: 4 |
Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 10BASE-T |
Copper ethernet cabling technology: 100BASE-FX | Switch layer: L2 | Basic switching RJ-45 Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

ports quantity: 5 | VLAN support: Yes | Copper ethernet cabling technology: 1000BASE-T | User guide: Yes | Number of VLANs: 4000 | 10G support: No | Flow control support: Yes | Virtual LAN features: Port-based VLAN | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Virtual LAN features: Tagged VLAN | Depth: 98 mm | LED indicators: Status | LED indicators: Link | Input current: 1.31 A | LED indicators: Speed | LED indicators: Activity | LED indicators: PoE | LED indicators: Power | Operating relative humidity (H-H): 10 - 90% | Package weight: 770 g | Input voltage: 53.5 V | Power over Ethernet (PoE): Yes | Package depth: 196 mm | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3af | Web-based management: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power consumption (max): 75.16 W | Package width: 131 mm | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3at | Product colour: Black | Storage relative humidity (H-H): 5 - 95%

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950