

TP-Link Omada 24-Port Gigabit L2+ Managed Switch with 4 SFP Slots



Model: SG3428

Manufacturer: TP-LINK

EAN: 1210002611886

Product Code: 960659

R4,962

Cables included: LAN (RJ-45) | Height: 44 mm | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Operating temperature (T-T): 0 - 45 °C | Storage relative humidity (H-H): 5 - 90% | Switching capacity: 56 Gbit/s | Power over Ethernet (PoE): No | Width: 440 mm | DHCP features: DHCP server | Rack mounting: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | Form factor: 1U | IPv6 routes: 48 | Packet buffer memory: 12 MB | IPv4 routes: 48 | MAC address table: 16000 entries | Operating relative humidity (H-H): 10 - 90% | Depth: 180 mm | Power consumption (max): 20.6 W | Jumbo frames support: Yes | Power source: AC | SFP module slots quantity: 4 | Power supply included: No | Number of fans: 0 fan(s) | 10G support: No | Number of VLANs: 4000 | AC input frequency: 50/60 Hz | Web-based management: Yes | MAC address filtering: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.3ab | LED indicators: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Networking standards:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

IEEE 802.3i | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3u | IGMP snooping: Yes | AC input voltage: 100 - 240 V | Quick start guide: Yes | DHCP features: DHCP snooping | DHCP features: DHCPv6 snooping | DHCP features: DHCPv6 client | Port mirroring: Yes | Heat dissipation: 70.3 BTU/h | Product colour: Black | Switch type: Managed | Multicast support: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | IP routing: Yes | Loop protection: Yes | Access Control List (ACL): Yes | Static route: Yes | Authentication type: AAA, RADIUS, TACACS+ | Static port security: Yes | Virtual LAN features: Voice VLAN | Switch layer: L2/L3 | Virtual LAN features: Private VLAN | System event log: Yes | IPv4 & IPv6 features: IPv6 Telnet | Virtual LAN features: Tagged VLAN | Forwarding rate: 41.66 Mpps | Authentication: MAC-based authentication, Port-based authentication | Console port: RJ-45/micro-USB | Cloud-managed: Yes | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | IPv4 & IPv6 features: IPv6 traceroute | Policy-based routing: Yes | Rate limiting: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Yes | Link aggregation: Yes | Store-and-forward: Yes | Flow control support: Yes | MIB support: Yes | Configuring Location Settings (CLI): Yes | SSH/SSL support: Yes | GARP VLAN Registration Protocol (GVRP): Yes | IP-MAC-Port binding: Yes | Virtual LAN features: Protocol-based VLAN | Gigabit Ethernet (copper) ports quantity: 24 | Spanning tree protocol: Yes | Jumbo frames: 9000 | BPDU filtering/protection: Yes | Number of static routes: 48 | ARP inspection: Yes | IPv4 & IPv6 features: IPv6 ping | Head-of-line (HOL) blocking: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950