

TP-Link Omada 24-Port Gigabit and 4-Port 10GE SFP+ L2+ Managed Switch with 24-Port PoE+



Model: SG3428XMP

Manufacturer: TP-LINK

EAN: 1210002611619

Product Code: 961330

R10,915

Networking standards: IEEE 802.1w | Number of fans: 2 fan(s) | Web-based management: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Power source: AC | Rack mounting: Yes | Width: 440 mm | Form factor: 1U | Operating relative humidity (H-H): 10 - 90% | Power over Ethernet (PoE): Yes | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.11d | Total Power over Ethernet (PoE) budget: 384 W | Networking standards: IEEE 802.1s | AC input voltage: 100 - 240 V | LED indicators: Yes | Quick start guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 45 °C | Power consumption (max): 486.2 W | Product colour: Black | Depth: 330 mm | Height: 44 mm | Cables included: LAN (RJ-45) | Broadcast storm control: Yes | VLAN support: Yes | Number of static

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

routes: 48 | Jumbo frames support: Yes | IP-MAC-Port binding: Yes | Forwarding rate: 95.23 Mpps | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 24 | System event log: Yes | Gigabit Ethernet (copper) ports quantity: 24 | DHCP features: DHCPv6 client | Switch layer: L2+ | DHCP features: DHCP snooping | Basic switching RJ-45 Ethernet ports quantity: 24 | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCPv6 snooping | DHCP features: DHCP server | Head-of-line (HOL) blocking: Yes | Link aggregation: Yes | MIB support: Yes | Switching capacity: 128 Gbit/s | Rate limiting: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Virtual LAN features: Tagged VLAN | Virtual LAN features: Voice VLAN | Multicast support: Yes | Virtual LAN features: MAC address-based VLAN | Virtual LAN features: Private VLAN | Port mirroring: Yes | Virtual LAN features: Protocol-based VLAN | BPDU filtering/protection: Yes | Heat dissipation: 1658.78 BTU/h | Virtual LAN features: Port-based VLAN | MAC address table: 16000 entries | Policy-based routing: Yes | IGMP snooping: Yes | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | Loop protection: Yes | Console port: RJ-45/micro-USB | Cloud-managed: Yes | Packet buffer memory: 12 MB | Switch type: Managed | Active link detection: Yes | Management protocols: SNMPv1/v2c/v3, SNTTP | Power supply included: Yes | SSH/SSL support: Yes | Number of VLANs: 4000 | 10G support: Yes | Flow control support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950