

## **TP-Link TL- SG108 network switch Unmanaged L2 Gigabit Ethernet (10/100/1000) Black**



Model: TL-SG108

Manufacturer: TP-LINK

EAN: 1210002616898

Product Code: 964805

## **R1,155**

Certification: CE, FCC ,RoHS | MAC address table: 4096 entries | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Copper ethernet cabling technology: 100BASE-TX | GARP VLAN Registration Protocol (GVRP): Yes | Width: 158 mm | Cables included: AC | Full duplex: Yes | IGMP snooping: Yes | Harmonized System (HS) code: 85176990 | MAC address auto-aging supported: Yes | Storage relative humidity (H-H): 5 - 90% | Basic switching RJ-45 Ethernet ports quantity: 8 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 1000BASE-T | MAC address auto-learning supported: Yes | Wall mountable: Yes | Cable types supported: Cat4 | Forwarding rate: 11.9 Mpps | Switching capacity: 16 Gbit/s | Power consumption (max): 3.3 W | Store-and-forward: Yes | Jumbo frames support: Yes | Jumbo frames: 16000 | Quality of Service (QoS)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

support: Yes | Cable types supported: Cat3 | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | Auto-negotiation: Yes | 10G support: No | Flow control support: Yes | User guide: Yes | Switch layer: L2 | Cable types supported: Cat5 | Cable types supported: Cat5e | Manual: Yes | Access Control List (ACL) IPv6 entries: 11 | Height: 25 mm | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | Rack mounting: No | Depth: 101 mm | Multicast support: Yes | Switch type: Unmanaged | Input current: 0.6 A | LED indicators: Yes | AC input voltage: 220 V | Storage temperature (T-T): -40 - 70 °C | Networking standards: IEEE 802.3x | Package type: Box | Operating temperature (T-T): 0 - 40 °C | Product colour: Black | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | AC input frequency: 50 Hz | Quick start guide: Yes | Power over Ethernet (PoE): No

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950