

TP-Link TL- SG1016PE network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black



Model: TL-SG1016PE

Manufacturer: TP-LINK

EAN: 1210002616775

Product Code: 966015

R3,449

Certification: FCC, CE, RoHS | Gigabit Ethernet (copper) ports quantity: 16 | Power consumption (max): 124.4 W | Power over Ethernet plus (PoE+) ports quantity: 8 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Switching capacity: 32 Gbit/s | Number of fans: 1 fan(s) | Jumbo frames support: Yes | Link aggregation: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Store-and-forward: Yes | Web-based management: Yes | Broadcast storm control: Yes | Cable types supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Cat5 | Jumbo frames: 10000 | Rate limiting: Yes | Height: 44 mm | Cable types supported: Cat3 | Cable types supported: Cat6 | Depth: 180 mm | Stackable: No | Virtual LAN features: Tagged VLAN | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | LED indicators: Yes | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.3u | Storage relative humidity (H-H): 5 - 90% | Rack mounting: Yes | IGMP snooping: Yes | Cables included: AC | Cable types supported: Cat4 | Cable types supported: Cat5e | Loop protection: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | AC input voltage: 100 - 240 V | Harmonized System (HS) code: 85176990 | Number of queues: 4 | Port mirroring: Yes | Auto MDI/MDI-X: Yes | Width: 294 mm | Throughput: 23.8 Mpps | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.3at | Switch type: Managed | Virtual LAN features: Port-based VLAN | Full duplex: Yes | Power supply included: Yes | Operating relative humidity (H-H): 10 - 90% | Static port security: Yes | Switch layer: L2 | Number of VLANs: 4000 | Rack mount kit: Yes | Flow control support: Yes | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE) budget: 150 W | AC input frequency: 50 - 60 Hz | Copper ethernet cabling technology: 100BASE-TX | 10G support: No | VLAN support: Yes | Copper ethernet cabling technology: 10BASE-T | Product colour: Black | Copper ethernet cabling technology: 1000BASE-T | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports quantity: 16

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950