CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-10-30 11:58

Intellinet 24-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports IEEE 802.3at/af (PoE+/PoE) Compliant, 370 W PoE Power Budget, Two 1G SFP Open Slots, Self-Healing Network, 19" Rackmount

Model: 561907

Manufacturer: INTELLINET

EAN: 766623561907

Product Code: 973587

R9,068

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power over Ethernet Switch with 26 ports - 24 RJ45 and Two SFP, High-Power PoE+, PD Alive, VLAN and PoE Extend Mode

The Intellinet Network Solutions 24-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports passes both data and electrical power to a number of PoE-compatible devices via standard Cat5e or Cat6 network cables. Equipped with 24 Gigabit Ethernet ports, this switch can power wireless LAN access points and bridges, VoIP phones, IP video cameras and more while delivering network speeds up to 1,000 Mbps.

Power over Ethernet 802.3at

This high-powered switch supports the IEEE 802.3at protocol and can inject up to 30 watts of power per port. IEEE802.3af- or IEEE802.3at-compliant devices attached to the switch need no additional power to help avoid the time and expense of electrical rewiring and minimize the unsightly clutter of power supplies and adapters on ceilings and walls. Any mix of PoE and non-PoE devices is supported, and thanks to its short-circuit, overload and high-voltage protection function, your equipment is well-protected. For devices that are not 802.3at/af compliant (legacy wireless access points or network cameras), we suggest the use of an Intellinet Network Solutions PoE/PoE+ Splitter.

Eliminate Bottlenecks with 26 Gigabit Ports

Equipped with 24 auto-sensing 10/100/1000 Mbps RJ45 Gigabit Ethernet ports, this switch offers plenty of performance for your computers, servers and other networking devices. In addition, two small form-factor pluggable (SFP) GBIC module slots provide fiber connectivity for greater distances. These are not shared combo-ports but true Gigabit ports, pushing the total available bandwidth up to 52 Gbps.

Self-Healing Network with increased reliability and stability - Intellinet Powered Device Monitor (PDM)
This Power over Ethernet switch has a self-healing PoE function called "Powered Device Monitoring." This PoE watchdog does a PD alive check on all connected PDs and automatically resets devices that aren't responding, like PoE security cameras, by cutting power and then turning it back on. The PDM function is especially useful in industrial or surveillance settings where devices connected to the network are important to how it works. As an added bonus, the PD Alive function helps cut down on

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

unnecessary technical support calls and expensive field trips by field-support engineers. This is because the functional reboot can often bring the unresponsive device back online.

PoE Extend Mode ideal for IP cameras

Selectable with a convenient slide switch on the front panel, you can manually activate a "PoE Extend Mode" that reduces your network speed and extends your PoE range up to 250 m (820 ft.), which is ideal to deliver power and data to IP cameras over longer distances.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950