



QNAP QSW-M2106R-2S2T network switch Managed L2 10G Ethernet (100/1000/10000) 1U Black

Model: QSW-M2106R-2S2T

Manufacturer: QNAP

EAN: 4711103082799

Product Code: 973804

R12,790

The QSW-M2106R-2S2T is a Layer 2 Web Managed Switch with two 10GbE SFP+ fiber ports, two 10GbE RJ45 ports and six 2.5GbE RJ45 ports. Supporting Layer 2 switching and network management via a user-friendly web user interface, the QSW-M2106R-2S2T offers flexible deployment in hybrid high-speed network environments and provides an entry-level network management solution. With a half-width design, two QSW-M2106R-2S2T can be installed in a 1U rack space for space-saving.

10GbE connectivity

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Includes two 10GbE SFP+ fiber ports (Backward compatible with 1G SFP) and two 10GbE RJ45 ports, compatible with NBASE-T technologies to support five speeds (10G / 5G / 2.5G / 1G / 100M) for high-speed networks.

2.5GbE connectivity

Six 2.5GbE RJ45 ports allow you to immediately multiply your network speed by 2.5 times while using existing Cat 5e cables.

User-friendly management interface

The QNAP Switch System (QSS) is easy to use and provides an overview dashboard, port management and setting guide, making central network management intuitive.

Layer 2 network

Provides Layer 2 management features (such as LACP, VLAN, ACL and LLDP) for IT staff to efficiently control network bandwidth and enhance security.

RSTP

One of the few web-managed switches that supports Rapid Spanning Tree Protocol (RSTP). Easily and efficiently deploy small/medium-scale networks that support expansion, redundancy, and loop prevention.

Online firmware update

QSS can be updated with just one click, helping IT staff ensure their network security.

Half-width design, two models in 1U

With a half-width rackmount design, a QSW-M2106R-2S2T can be installed in a 1U rack space with another half-width rackmount switch (such as QSW-M2108R-2C) for efficient physical space utilization and tidy cabling.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Flexible deployment with multiple 10G SFP+ fiber and Gigabit ports

The QSW-M2106R-2S2T provides two 10GbE SFP+ ports, two 10GbE RJ45 ports and six 2.5 Gigabit ports for connecting various devices and enabling hybrid high-speed networks. With SFP+ interfaces, Direct Attach Copper (DAC) cables can be used for connecting directly to SFP+ devices. You can also use RJ45 ports to connect 10GBASE-T/NBASE-T™ devices through RJ45 Category 6a (or better) cabling. The switching capacity of the QSW-M2106R-2S2T is 110Gbps, guaranteeing the full potential of each port.