CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-11-18 04:17



Mercusys 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router

Model: MB230-4G

Manufacturer: MERCUSYS

EAN: 6957939001827

Product Code: 987055

R2,086

Receiver sensitivity: 11g 6Mbps: -95dBm 11g 54Mbps: -77dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: -71dBm 11a 6Mbps: -92dBm 11a 54Mbps: -75dBm 11ac VHT20 MCS8: -70dBm 11ac VHT40 MCS9: -65dBm 11ac VHT80 MCS9: -61dBm | Indication light: Yes | Security algorithms: WPA2-PSK | WPS push button: Yes | Security algorithms: 64-bit WEP | Depth: 61 mm | SIM card slot: Yes | Ethernet LAN data rates: 100 | Product type: Desktop/pole router | UMTS bands supported: 850 | Antenna design: Internal | Ethernet LAN data rates: 1000 | DSL WAN: No | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | WLAN data transfer rate (max): 1200 Mbit/s | Security algorithms: WPA3-SAE | Operating relative humidity (H-H): 10 - 90% | VoIP protocols: IPv4, IPv6 | Port-based Network Access Control (PNAC): Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11g | UMTS bands supported: 900 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi Multimedia (WMM)/(WME): Yes | Dual SIM support: No | 4G bands supported: 2600 MHz | 4G bands supported: 850 | Networking

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

standards: IEEE 802.11b | 4G bands supported: 2100 | 4G bands supported: 800 | Cabling technology: 10/100/1000Base-T(X) | Universal Plug and Play (UPnP): Yes | UMTS bands supported: 2100 | Mobile network generation: 4G | WAN connection type: RJ-45 | Ethernet WAN: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Output voltage: 12 V | SIM card type: NanoSIM | Width: 95 mm | Ethernet LAN: Yes | System event log: Yes | Ethernet LAN (RJ-45) ports: 2 | Firewall: Yes | Height: 166 mm | 3G/4G USB modem compatibility: Yes | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Quick installation guide: Yes | Networking standards: IEEE 802.11a | 4G bands supported: 900 | USB port: No | 3G standards: UMTS | 4G bands supported: 700 | 4G bands supported: 2300 | Power source type: DC | DC-in jack: Yes | Wi-Fi standards: 802.11b | Operating temperature (T-T): 0 - 40 °C | Number of products included: 1 pc(s) | 4G standard: LTE-TDD & LTE-FDD | 3G standards: HSPA | Output current: 1 A | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Product colour: White | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | 4G bands supported: 1800 | Wi-Fi standards: 802.11a | Networking standards: IEEE 802.11ac | DHCP server: Yes | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Port triggering: Yes | Port forwarding: Yes | Package type: Box | DMZ support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950