



TP-Link Omada 5-Port Gigabit Easy Managed Switch with 4- Port PoE+



Model: ES205GP

Manufacturer: TP-LINK

EAN: 8885020620931

Product Code: 987057

R1,652

IGMP snooping: Yes | Power over Ethernet (PoE): Yes | Total Power over Ethernet (PoE) budget: 65 W | Operating temperature (T-T): 0 - 40 °C | Switch type: Managed | Height: 25 mm | Loop protection: Yes | Switching capacity: 10 Gbit/s | MAC address table: 8000 entries | Auto-negotiation: Yes | Power supply included: Yes | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Depth: 98 mm | Power over Ethernet (PoE) ports quantity: 4 | Wall mountable: Yes | Operating relative humidity (H-H): 10 - 90% | Width: 100 mm | LED indicators: Yes | Port mirroring: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.1p | Product colour: Black | Networking standards: IEEE 802.3at | Flow control support: Yes | 10G support: No | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Store-and-forward: Yes | Power source: AC/DC | Jumbo frames support: Yes | Reset button: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

DHCP features: DHCP client | Basic switching RJ-45 Ethernet ports quantity: 5 | Package type: Box | VLAN support: Yes | Power over Ethernet plus (PoE+) ports quantity: 4 | Cloud-managed: Yes | DC input voltage: 53.5 V | Virtual LAN features: MTU VLAN | Link aggregation: Yes | Jumbo frames: 15 | Fanless: Yes | Transmission distance (max): 0.25 km | Virtual LAN features: Port-based VLAN | Virtual LAN features: Tagged VLAN | Forwarding rate: 7.4 Mpps | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself. | Warnings: Ensure the unit is adequately ventilated during operation. | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950