

Ubiquiti U7 Outdoor 4300 Mbit/s White Power over Ethernet (PoE)

Ubiquiti U7 Outdoor 4300 Mbit/s White Power over Ethernet (PoE)



Model: U7-Outdoor

Manufacturer: UBIQUITI

EAN: 810084695531

Product Code: 987164

R5,173

Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.11be | Security algorithms: WPA-Enterprise | Height: 208 mm | Number of connectors: 2 | Ethernet LAN data rates: 2500 Mbit/s | 2.4 GHz: Yes | 5 GHz: Yes | Networking standards: IEEE 802.11ac | Depth: 54.5 mm | Antenna features: Detachable antenna | Operating relative humidity (H-H): 5 - 95% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | MIMO: Yes | Antenna connector type: RP-SMA | Housing material: Aluminium, Polycarbonate (PC) | Frequency band: 2.4 - 5 GHz | Mounting kit: Yes | Antenna direction type: Omni-directional | VLAN support: Yes | Product colour: White | Antenna type: External | Power over Ethernet (PoE): Yes | Security algorithms: WPA2 | Throughput data rate: 4324 Mbit/s | Width: 170 mm | Security algorithms: WPA | Recommended usage: Outdoor | Antenna gain level (max): 12.5 dBi | Security algorithms: WPA-PSK | Security algorithms: WPA3 | Quantity per pack: 1 pc(s) | Weight:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

1.2 kg | Maximum data transfer rate: 4300 Mbit/s | Power consumption (max): 19 W | Security algorithms: PPSK | Placement: Ceiling, Pole, Wall | Reset button: Yes | International Protection (IP) code: IPX6 | Antennas quantity: 2 | MIMO type: Multi User MIMO | LED indicators: Yes | Ethernet LAN (RJ-45) ports: 1 | Rate limiting: Yes | Operating temperature (T-T): -30 - 60 °C | DC voltage range: 44 - 57 V | Quality of Service (QoS) support: Yes | Warnings: Avoid contact with liquids - the unit is not waterproof. | Warnings: Do not dismantle the appliance - internal components may be hazardous to the user's health and should only be handled by qualified personnel. | Warnings: Risk of electric shock - use caution during installation and use. | Spatial streams: 4 | 6 GHz: No | Sustainability compliance: Yes | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: Industry Canada (IC) | Compliance certificates: CE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950