

TP-Link 8-Port Gigabit Desktop Network Switch



Model: TL-SG1008D

Manufacturer: TP-LINK

EAN: 1210002616645

Product Code: 988078

R1,019

Certification: CE, FCC, RoHS | Power consumption (max): 3.53 W | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3x | Operating temperature (T-T): 0 - 40 °C | Width: 180 mm | Cables included: AC | Package weight: 300 g | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90% | Power source: DC | Ethernet LAN data rates: 10,100,480,800,1000 Mbit/s | Package width: 110 mm | Package height: 85 mm | Package type: Box | AC input frequency: 50/60 Hz | AC input voltage: 100 - 240 V | LED indicators: Yes | AC adapter included: Yes | Switching capacity: 16 Gbit/s | Power connector: DC-in jack | Product colour: Black | Package depth: 185 mm | User guide: Yes | Input current: 0.6 A | Gigabit Ethernet (copper) ports quantity: 8 | Rack mounting: No | Store-and-forward: Yes | Storage temperature (T-T): -40 - 70 °C | Full duplex: Yes | Height: 25.5 mm | Stackable: No | Depth: 90 mm | Jumbo frames support: Yes | Harmonized System (HS) code: 85176990 | Packet forwarding rate (10 Mbps): 1488000 pps | Housing material: Plastic | Jumbo frames: 15000 | Packet forwarding rate (1 Gbps): 14880 pps | Packet buffer memory: 2 MB | Auto-negotiation: Yes | Maximum cable length: 100 m | Power supply included: Yes | Wall mountable: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Cable types supported: Cat4 | MAC address table: 4000 entries | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Power consumption (typical): 4.63 W | Fanless: Yes | DC input voltage: 9 V | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 1000BASE-T | Cable types supported: Cat5 | Cable types supported: Cat5e | Copper ethernet cabling technology: 100BASE-TX | Auto MDI/MDI-X: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Heat dissipation: 15.8 BTU/h | Switch type: Unmanaged | Cable types supported: Cat3 | Packet forwarding rate (100 Mbps): 148800 pps | 10G support: No | Flow control support: Yes | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Sustainability compliance: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950