



TP-Link 8-Port Gigabit Easy Smart Switch with 4-Port PoE



Model: TL-SG108PE

Manufacturer: TP-LINK

EAN: 1210002616942

Product Code: 988079

R1,833

Certification: FCC, CE, RoHS | MAC address table: 4000 entries | Basic switching RJ-45 Ethernet ports quantity: 8 | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | Input current: 1.25 A | AC input voltage: 220 V | LED indicators: Link | LED indicators: Activity | LED indicators: Power | LED indicators: Speed | Power over Ethernet plus (PoE+) ports quantity: 4 | Rate limiting: Yes | Switching capacity: 16 Gbit/s | Power source: DC | Power consumption (max): 65.2 W | Package type: Box | Package height: 121 mm | Cables included: AC | Operating relative humidity (H-H): 10 - 90% | Package weight: 860 g | VLAN support: Yes | LED indicators: PoE | AC input frequency: 50 Hz | Broadcast storm control: Yes | Port mirroring: Yes | Switch layer: L2 | Store-and-forward: Yes | Web-based management: Yes | Jumbo frames support: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Package width: 131 mm | LED indicators: Status | Power over Ethernet (PoE) ports quantity: 4 | Power supply included: Yes | Heat dissipation: 256.19 BTU/h | Total Power over Ethernet (PoE) budget: 64 W | Height: 25 mm | Switch type: Managed | Loop protection: Yes | Operating temperature (T-T): 0 - 40 °C | Harmonized System (HS) code: 85176990 | Virtual LAN features: Port-based VLAN | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 5 -

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

95% | Depth: 101 mm | Auto-negotiation: Yes | Link aggregation: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power over Ethernet (PoE) power per port: 15.4 W | IGMP snooping: Yes | Networking standards: IEEE 802.3u | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Input voltage: 48 V | Width: 158 mm | Power over Ethernet (PoE): Yes | Product colour: Black | Number of VLANs: 32 | 10G support: No | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 196 mm | Gigabit Ethernet (copper) ports quantity: 8 | Jumbo frames: 15000 | Packet forwarding rate (1 Gbps): 11900000 pps | Cable types supported: Cat3 | Forwarding rate: 11.9 Mpps | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat6 | Cable types supported: Cat4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950