



TP-Link Omada 52-Port Gigabit L2+ Managed Switch with 48- Port PoE+



Model: TL-SG3452P

Manufacturer: TP-LINK

EAN: 1210002611947

Product Code: 988080

R13,777

AC input voltage: 100 - 240 V | AC input frequency: 50/60 Hz | Product colour: Black | Ethernet LAN data rates: 10,100,1000 Mbit/s | Networking standards: IEEE 802.1p | Web-based management: Yes | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1w | LED indicators: Yes | Height: 44 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power consumption (max): 464.2 W | Switching capacity: 104 Gbit/s | Cables included: AC | Width: 440 mm | Rack mounting: Yes | Quick start guide: Yes | SFP module slots quantity: 4 | Form factor: 1U | Power source: AC | Power over Ethernet (PoE): Yes | Manual: Yes | Number of fans: 3 fan(s) | Power over Ethernet (PoE) power per port: 30 W | Storage relative humidity (H-H): 5 - 90% | Total Power over Ethernet (PoE) budget: 384 W | Operating temperature (T-T): 0 - 40 °C | Reset button: Yes | Package type: Box | VLAN support: Yes | Depth: 330 mm | Jumbo frames support: Yes | Password protection: Yes | Power supply included: Yes | Operating relative humidity (H-H): 10 - 90% |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Basic switching RJ-45 Ethernet ports quantity: 48 | ARP inspection: Yes | Virtual LAN features: MAC address-based VLAN | Port mirroring: Yes | Access Control List (ACL): Yes | SSH/SSL support: Yes | Loop protection: Yes | Static route: Yes | Number of VLANs: 4000 | Heat dissipation: 1584.08 BTU/h | Multicast support: Yes | Virtual LAN features: Private VLAN | Authentication: MAC-based authentication, Port-based authentication | Virtual LAN features: Voice VLAN | 10G support: No | Virtual LAN features: Tagged VLAN | Policy-based routing: Yes | IGMP snooping: Yes | Rate limiting: Yes | Virtual LAN features: Protocol-based VLAN | Forwarding rate: 77.38 Mpps | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 48 | Switch type: Managed | Active link detection: Yes | Packet buffer memory: 12 MB | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | MAC address table: 16000 entries | DHCP features: DHCP snooping | Spanning tree protocol: Yes | Jumbo frames: 9000 | IP routing: Yes | Link aggregation: Yes | BPDU filtering/protection: Yes | Switch layer: L2/L3 | DHCP features: DHCP client | DHCP features: DHCP relay | Store-and-forward: Yes | MIB support: Yes | Console port: RJ-45/micro-USB | Cloud-managed: Yes | GARP VLAN Registration Protocol (GVRP): Yes | DHCP features: DHCPv6 snooping | Broadcast storm control: Yes | Flow control support: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | DHCP features: DHCPv6 client | DHCP features: DHCP server | System event log: Yes | Number of static routes: 48 | Head-of-line (HOL) blocking: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950