



TP-Link 18-Port Gigabit Rackmount Switch with 16 PoE+



Model: TL-SG1218MP

Manufacturer: TP-LINK

EAN: 1210002617086

Product Code: 988081

R4,510

Certification: CE, FCC, RoHS | AC input voltage: 100 - 240 V | Number of fans: 2 fan(s) | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Gigabit Ethernet (copper) ports quantity: 18 | Jumbo frames: 10000 | Height: 44 mm | Storage relative humidity (H-H): 5 - 90% | Package weight: 3.05 kg | Cables included: AC | AC input frequency: 50 - 60 Hz | Package width: 250 mm | MAC address table: 8000 entries | Auto-negotiation: Yes | Half duplex: Yes | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE): Yes | Full duplex: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Rack mounting: Yes | Packet buffer memory: 4.1 MB | Housing material: Metal | MAC address auto-learning supported: Yes | Package height: 80 mm | Power supply included: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Switching capacity: 36 Gbit/s | Operating relative humidity (H-H): 10 - 90% | Power consumption (max): 286.64 W | Power over Ethernet plus (PoE+) ports quantity: 16 | Width: 440 mm | Total Power over Ethernet (PoE) budget:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

250 W | Jumbo frames support: Yes | Operating temperature (T-T): 0 - 50 °C | Depth: 180 mm | Quick start guide: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Basic switching RJ-45 Ethernet ports quantity: 18 | LED indicators: Yes | Forwarding rate: 26.78 Mpps | Auto MDI/MDI-X: Yes | Form factor: 1U | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat3 | Cable types supported: Cat6 | Heat dissipation: 977.44 BTU/h | Combo SFP ports quantity: 2 | Power source: AC | Cable types supported: Cat4 | Product colour: Black | Traffic classification: Yes | MAC address auto-aging supported: Yes | Switch type: Unmanaged | Flow control support: Yes | 10G support: No | Package depth: 528 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950