

Ubiquiti Dream Machine Pro Max gateway/controller 10, 100, 1000, 2500 Mbit/s

Ubiquiti Dream Machine Pro Max gateway/controller 10, 100, 1000, 2500 Mbit/s



Model: UDM-Pro-Max

Manufacturer: UBIQUITI

EAN: 810084693254

Product Code: 988444

R14,646

Port aggregation: Yes | Electrostatic Discharge (ESD) protection (contact): 8 kV | SFP+ ports quantity: 2 | Enclosure material: Aluminium/SGCC | Electromagnetic (EMP) protection: Yes | Electromagnetic (EMP) protection (contact): 8 kV | Warnings: Do not use in damp conditions. | Electromagnetic (EMP) protection (air): 15 kV | Electrostatic Discharge (ESD) protection (air): 15 kV | Warnings: Make sure the unit is stably mounted and ventilated. | Warnings: Do not open the appliance - risk of electric shock. | Compliance certificates: Industry Canada (IC) | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | WAN connection: Ethernet (RJ-45), SFP+ | Product colour: Grey | Mounting type: Rack mounting | Quality of Service (QoS) support: Yes | DC input voltage: 12 V | Internal memory: 8000 MB | Operating temperature (T-T): -10 - 40 °C | Cables included: AC | Routing protocols: BGP | Height: 43.7 mm | Number of processors installed: 1 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet LAN data rates: 1000 Mbit/s | Built-in processor: Yes | Weight: 4.7 kg | Power consumption (max): 60 W | Ethernet LAN data rates: 100 | Processor frequency: 2000 MHz | Input frequency: 50/60 Hz | Ethernet LAN data rates: 2500 Mbit/s | Processor model: Cortex-A57 | Reset button: Yes | Power over Ethernet (PoE): No | Width: 442.4 mm | Flash memory: 32000 MB | DHCP server: Yes | Rack capacity: 1U | Ethernet LAN (RJ-45) ports: 9 | VLAN support: Yes | LED indicators: Activity | LED indicators: Link | Ethernet LAN data rates: 10 | SSD capacity: 128 GB | Routing protocols: OSPF | Display type: LCM | Control display unit: Yes | Operating relative humidity (H-H): 5 - 95% | LED indicators: Error | Firewall security: Yes | Depth: 285.6 mm | Multicast support: Yes | Input current: 2 A | Processor family: ARM Cortex | LED indicators: Ready | Input voltage: 100 - 240 V | Processor manufacturer: ARM | Heat dissipation: 205 BTU/h

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950