

TP-LINK Archer C6 wireless router Fast Ethernet Dual-band (2.4 GHz 5 GHz) 4G White

TP-LINK Archer C6 wireless router Fast Ethernet Dual- band (2.4 GHz 5 GHz) 4G White



Model: Archer C6

Manufacturer: TP-LINK

EAN: 1210002606523

Product Code: 988624

R1,402

VPN support: PPTP, L2TP, IPSec | Receiver sensitivity: 5GHz: 11a 54M: -76dBm 11ac VHT20 MCS8: -70dBm 11ac VHT40 MCS9: -65.5dBm 11ac VHT80 MCS9: -61.5dBm 2.4G: 11g 54M: -76dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: -71dBm | MAC address filtering: Yes | 3G: No | DC-in jack: Yes | Product colour: White | AC adapter included: Yes | Package type: Box | Filtering: Yes | Operating relative humidity (H-H): 10 - 90% | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows 10 Education x64 | Windows operating systems supported: Windows XP Home

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

x64 | Package weight: 870 g | Windows operating systems supported: Windows 10 Enterprise x64 | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Quick start guide: Yes | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows Vista Home Basic x64 | Reset button: Yes | Storage temperature (T-T): -40 - 70 °C | Maximum data transfer rate: 1 Mbit/s | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 8.1 Enterprise | 4G: No | Stateful Packet Inspection (SPI): Yes | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows 10 Education | Windows operating systems supported: Windows XP Professional | Ethernet LAN (RJ-45) ports: 5 | Operating temperature (T-T): 0 - 40 °C | DHCP client: Yes | Package width: 350 mm | Windows operating systems supported: Windows Vista Home Basic | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 | Power source type: AC | LED indicators: LAN, Power, WLAN | Security algorithms: 128-bit WEP | Security algorithms: WPA2-PSK | Security algorithms: WPA | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11ac | Output voltage: 12 V | Cabling technology: 10/100Base-T(X) | VoIP protocols: IPv4, IPv6 | On/off switch: Yes | Indication light: Yes | Antennas quantity: 5 | Firewall: Yes | Guest access: Yes | Universal Plug and Play (UPnP): Yes | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Windows operating systems supported: Windows 7 Professional x64 | Port forwarding: Yes | DHCP server: Yes | Windows operating systems supported: Windows 10 Pro x64 | Windows operating systems supported: Windows 8 Enterprise | Antenna design: External | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Ethernet LAN interface type: Fast Ethernet | Transmit power: CE: 20dBm(2.4GHz), 23dBm(5GHz) |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows XP Professional x64 | Harmonized System (HS) code: 85176990 | DoS attack prevention: Yes | Width: 215 mm | WLAN data transfer rate (second band): 867 Mbit/s | WAN connection type: RJ-45 | USB port: No | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | DMZ support: Yes | DSL WAN: No | Output current: 1 A | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Linux operating systems supported: Yes | Memory card slot(s): No | WPS push button: Yes | Depth: 117 mm | IP address filtering: Yes | Ethernet LAN: Yes | SIM card slot: No | Product type: Tabletop router | Height: 32 mm | 3G/4G USB modem compatibility: No | VPN Passthrough: Yes | WLAN data transfer rate (first band): 450 Mbit/s | Cables included: LAN (RJ-45) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Ethernet WAN: Yes | Mac compatibility: Yes | Package depth: 240 mm | Package height: 82 mm | Wi-Fi standards: 802.11b | Wi-Fi standards: 802.11g | Mac operating systems supported: MacOS | Wi-Fi standards: Wi-Fi 4 (802.11n) | Manual: Yes | Quick installation guide: Yes | WLAN data transfer rate (max): 867 Mbit/s | Wi-Fi standards: 802.11a

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950