



TP-Link Omada 16-Port Gigabit Smart Switch with 2 SFP Slots



Model: TL-SG2218

Manufacturer: TP-LINK

EAN: 1210002611824

Product Code: 988647

R3,893

Certification: CE, FCC, RoHS | Web-based management: Yes | Product colour: Black | Fanless: Yes | Number of IP interfaces: 16 | Cloud-managed: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Number of static routes: 32 | ARP inspection: Yes | Power over Ethernet (PoE): No | Width: 440 mm | Rack mounting: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | Networking standards: IEEE 802.3ab | DHCP features: DHCP snooping | IGMP snooping: Yes | Operating relative humidity (H-H): 10 - 90% | DHCP features: DHCPv6 snooping | Depth: 180 mm | MAC address table: 8000 entries | Package width: 250 mm | SFP module slots quantity: 2 | Jumbo frames support: Yes | Package weight: 2.45 kg | Operating temperature (T-T): 0 - 40 °C | DHCP features: DHCPv6 client | Power consumption (max): 12.3 W | Form factor: 1U | Power source: AC | VLAN support: Yes | Height: 44 mm | Cables included: LAN (RJ-45) | Basic switching RJ-45 Ethernet ports quantity: 16 | DHCP features: DHCP server | Cables included: AC | Switching capacity: 36 Gbit/s | AC input frequency: 50/60 Hz | Package height: 80 mm | Power supply included: Yes | AC input voltage: 100 - 240 V | Packet buffer memory: 4.1 MB | LED indicators: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | 10G support: No | Networking standards: IEEE 802.3u | Quick start guide: Yes | Networking

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

standards: IEEE 802.3z | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 528 mm | Storage relative humidity (H-H): 5 - 90% | Number of VLANs: 4000 | BPDU filtering/protection: Yes | Harmonized System (HS) code: 85176990 | Virtual LAN features: Voice VLAN | Spanning tree protocol: Yes | Jumbo frames: 9000 | Virtual LAN features: Private VLAN | Rate limiting: Yes | Port mirroring: Yes | Store-and-forward: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Link aggregation: Yes | Virtual LAN features: Port-based VLAN | Virtual LAN features: Protocol-based VLAN | Switch layer: L2/L2+ | System event log: Yes | Static route: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3i | MIB support: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | Virtual LAN features: Tagged VLAN | Switch type: Managed | Access Control List (ACL): Yes | Heat dissipation: 41.97 BTU/h | Forwarding rate: 26.8 Mpps | Flow control support: Yes | SSH/SSL support: Yes | Multicast support: Yes | Loop protection: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950