

Ubiquiti Dream Machine Beast gateway/controller 10, 100, 1000, 2500, 10000, 5000 Mbit/s

Model: UDM-BEAST

Manufacturer: UBIQUITI

EAN: 810177166559

Product Code: 988693

R35,558

Ethernet LAN (RJ-45) ports: 10 | Routing protocols: BGP | Number of processors installed: 1 | DC input voltage: 12 V | Number of console ports: 1 | SSD capacity: 128 GB | Routing protocols: OSPF | Firewall security: Yes | Processor frequency: 2100 MHz | Operating temperature (T-T): -10 - 40 °C | Operating relative humidity (H-H): 5 - 95% | Weight: 5.5 kg | WAN connection: Ethernet (RJ-45), SFP+ | Power consumption (max): 100 W | Product colour: Grey | Quality of Service (QoS) support: Yes | Height: 43.7 mm | Console port: RJ-45 | Enclosure material: Aluminium/SGCC | Rack capacity: 1U | Network address translation (NAT): Yes | Power over Ethernet (PoE): No | Display type: LCM | Cables included: AC | Processor family: ARM Cortex | Input frequency: 50/60 Hz | Control display unit: Yes | Ethernet LAN data rates: 100 | Width: 442.4 mm | Input voltage: 100 - 240 V | DHCP server: Yes | Reset button: Yes | Ethernet LAN data rates: 1000 | Ethernet LAN data rates: 5000 Mbit/s | Ethernet LAN data rates: 2500 | Built-in processor: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

rates: 10000 Mbit/s | Multicast support: Yes | Depth: 325 mm | Mounting type: Rack mounting | Internal memory: 16000 MB | Electromagnetic (EMP) protection (contact): 4 kV | Electromagnetic (EMP) protection (air): 8 kV | LED indicators: Error | Input current: 3 A | LED indicators: Link | LED indicators: Activity | Heat dissipation: 342 BTU/h | Processor manufacturer: ARM | LED indicators: Ready | SFP+ ports quantity: 2 | Electrostatic Discharge (ESD) protection (contact): 4 kV | Port aggregation: Yes | Electromagnetic (EMP) protection: Yes | Compliance certificates: Industry Canada (IC) | Electrostatic Discharge (ESD) protection (air): 8 kV | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: National Defense Authorization Act (NDAA)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950