

WIRELESS ROUTER TP-LINK TL-WR844N

WIRELESS ROUTER TP-LINK TL-WR844N



Model: TL-WR844N

Manufacturer: TP-LINK

EAN: 1210002616072

Product Code: 991085

R857

Certification: CE, RoHS | Built-in processor: Yes | WAN connection type: RJ-45 | DSL WAN: No | Depth: 106.7 mm | Ethernet LAN: Yes | SIM card slot: No | Output current: 0.6 A | Product type: Tabletop router | Height: 24.3 mm | 3G/4G USB modem compatibility: No | Firewall security: SPI Firewall, IP, MAC Address Binding | Port forwarding: Yes | Linux operating systems supported: Yes | DHCP server: Yes | Wi-Fi band: Single-band (2.4 GHz) | Dynamic DNS (DDNS): Yes | USB port: No | Memory card slot(s): No | Number of products included: 1 pc(s) | Firewall: Yes | DMZ support: Yes | Ethernet LAN data rates: 100 | Mac operating systems supported: Yes | Ethernet LAN data rates: 10 | Reset button: Yes | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 5 | 4G: No | Processor cores: 1 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | DHCP client: Yes | Power source type: AC | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows 7 | DC-in jack: Yes | Security algorithms: WPA | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Quick installation guide: Yes | Stateful Packet Inspection (SPI): Yes | Security algorithms: WPA2 | Product colour: White | AC adapter included: Yes | Security algorithms: WEP | Security algorithms: WPA2-PSK | WPS push button: Yes | WLAN data transfer rate

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(max): 300 Mbit/s | Output voltage: 5 V | Networking standards: IEEE 802.11b | Windows operating systems supported: Windows 8 | Wi-Fi standards: 802.11b | Ethernet WAN: Yes | Cabling technology: 10/100Base-T(X) | Width: 115 mm | Storage relative humidity (H-H): 5 - 90% | Guest access: Yes | Operating relative humidity (H-H): 10 - 90% | Antenna gain level (max): 5 dBi | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | 3G: No | Wi-Fi standards: Wi-Fi 4 (802.11n) | Windows operating systems supported: Windows 2000 | Port triggering: Yes | Windows operating systems supported: Windows XP | Cables included: LAN (RJ-45) | Antennas quantity: 2 | Ethernet LAN interface type: Fast Ethernet | Wi-Fi standards: 802.11g | Parental control: Yes | Antenna design: External

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950