



TP-Link 16-Port Gigabit Desktop Network Switch



Model: TL-SG116

Manufacturer: TP-LINK

EAN: 1210002616980

Product Code: 991522

R2,134

Forwarding rate: 23.81 Mpps | Operating relative humidity (H-H): 10 - 90% | Full duplex: Yes | Quick start guide: Yes | Switching capacity: 32 Gbit/s | Cables included: AC | Depth: 111.7 mm | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat3 | Power over Ethernet (PoE): No | Width: 286 mm | Wall mountable: Yes | Cable types supported: Cat6 | Cable types supported: Cat4 | Rate limiting: Yes | Rack mounting: No | Harmonized System (HS) code: 85176990 | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 4.1 MB | Port mirroring: Yes | Storage relative humidity (H-H): 5 - 90% | VLAN support: Yes | Heat dissipation: 31.68 BTU/h | Number of queues: 4 | Auto MDI/MDI-X: Yes | Housing material: Metal | Copper ethernet cabling technology: 100BASE-TX | IGMP snooping: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 1000BASE-T | DC input voltage: 9 V | Power supply included: Yes | Input current: 0.6 A | Loop protection: Yes | Switch type: Unmanaged | Height: 25.4 mm | Jumbo frames: 9000 | Jumbo frames support: Yes | Store-and-forward: Yes | Broadcast storm control: Yes | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Power consumption (max): 9.3 W | Operating temperature (T-T): 0 - 40 °C | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Virtual LAN features: Protocol-based VLAN |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Virtual LAN features: Tagged VLAN | Basic switching RJ-45 Ethernet ports quantity: 16 | LED indicators: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Number of VLANs: 32 | Cable length detection: Yes | 10G support: No | Flow control support: Yes | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Product colour: Black | AC input frequency: 50 Hz | AC input voltage: 220 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950