

Cudy LT400 wireless router Fast Ethernet Single-band (2.4 GHz) 4G White

Cudy LT400 wireless router Fast Ethernet Single-band (2.4 GHz) 4G White



Model: LT400 OUTDOOR_EU

Manufacturer: CUDY

EAN: 6971690792916

Product Code: 992244

R1,944

VPN support: PPTP/L2TP/OpenVPN/WireGuard/IPSec/Zerotier | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures. | Warnings: Do not expose the device to water or moisture. | PoE injector included: Yes | Filtering: Yes | Wake-on-LAN ready: Yes | Product colour: White | Antenna gain level (max): 5 dBi | Mounting kit: Yes | DHCP client: Yes | Operating temperature (T-T): -20 - 60 °C | Security algorithms: WPA3 | Ethernet LAN (RJ-45) ports: 1 | Security algorithms: WPA2 | AC input voltage: 100 - 240 V | Weight: 420 g | Power over Ethernet (PoE): Yes | MAC address filtering: Yes | Package width: 324 mm | Power source type: PoE | Modulation: 64-QAM | Ethernet LAN data rates: 10 | Operating relative humidity (H-H): 0 - 100% | Security algorithms: WPA | LED indicators: WLAN | Ethernet LAN data rates: 100 | Storage relative humidity (H-H): 5 - 95% | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows Vista

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Home Premium x64 | Windows operating systems supported: Windows 10 Education x64 | AC input frequency: 50/60 Hz | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems supported: Windows 8.1 Enterprise x64 | Windows operating systems supported: Windows 8.1 Pro x64 | Windows operating systems supported: Windows 8.1 x64 | Package weight: 794 g | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 10 IOT Core | Windows operating systems supported: Windows 8 Enterprise x64 | Windows operating systems supported: Windows 8 Pro | Windows operating systems supported: Windows 7 Enterprise | Windows operating systems supported: Windows 10 Pro x64 | Windows operating systems supported: Windows 8 Enterprise | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 10 Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows XP Professional x64 | Reset button: Yes | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 7 x64 | Windows operating systems supported: Windows XP Home x64 | Windows operating systems supported: Windows 10 Enterprise | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 8.1 Enterprise | Windows operating systems supported: Windows 7 Professional | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows 8 Pro x64 | Windows operating systems supported: Windows 8.1 Pro | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows 11 | Windows operating systems supported: Windows 10 Pro | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Windows operating systems supported: Windows 10 IoT Enterprise | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | Windows operating systems supported: Windows 11 Enterprise | Windows operating systems supported: Windows 10 Enterprise x64 | Windows operating systems supported: Windows 10 x64 | Windows operating systems supported: Windows 8 x64 | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows 10 Education |

Windows operating systems supported: Windows XP Professional | Windows operating systems

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: Windows XP | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows 10 Home x64 | Windows operating systems supported: Windows 8 | Storage temperature (T-T): -40 - 70 °C | Wi-Fi standards: 802.11b | WAN connection type: RJ-45 | Dual SIM support: No | Antennas quantity: 4 | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: Wi-Fi 4 (802.11n) | USB port: No | Mac operating systems supported: Yes | Product type: Desktop/pole router | SIM card type: NanoSIM | Wi-Fi standards: 802.11g | Package depth: 107 mm | Internal memory: 64 MB | 2G standards: Edge | SIM card slot: Yes | Dynamic DNS (DDNS): Yes | IGMP snooping: Yes | 4G standard: LTE-TDD & LTE-FDD | Port forwarding: Yes | Firewall: Yes | Width: 240 mm | Quick installation guide: Yes | Mobile network generation: 4G | Cables included: LAN (RJ-45) | Antenna design: Internal & external | Ethernet LAN interface type: Fast Ethernet | DMZ support: Yes | IP address filtering: Yes | Flash memory: 8 MB | Port triggering: Yes | 3G standards: WCDMA | Wall mountable: Yes | Number of guest networks (2.4 GHz): 1 | Supported network protocols: IPv4 / IPv6 | Linux operating systems supported: Yes | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Ethernet WAN: Yes | Package height: 86 mm | Height: 53.7 mm | Detachable antenna(s): Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | International Protection (IP) code: IP65 | Output voltage: 24 V | Universal Plug and Play (UPnP): Yes | Ethernet LAN: Yes | Depth: 100 mm | URL filtering: Yes | WLAN data transfer rate (max): 300 Mbit/s | Wi-Fi band: Single-band (2.4 GHz) | 2G standards: GSM

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950